FILTERS-MILITARY & CIVILIAN

(Gasoline, Mogas, E85, AVGAS)

POSSIBLE CONTAMINANS OF CONCERN

MOGAS may contain VOCs such as benzene, toluene, trimethylbenzene and xylene in varying levels. Refer to the MSDS for specific hazards.

CHARACTERIZATION

These used fuel filters are **Hazardous Wastes** and cannot be thrown in the dumpster.

CONTAINER MARKING AND HANDLING PROCEDURES

Step 1 If SAP is not established, turn in used fuel filters immediately upon generation. Contact the PPOC if a container is needed.

Step2 If the fuel filters will be accumulated on-site contact **Environmental Division Hazardous Waste** to establish a Satellite Accumulation Point (SAP) for hazardous waste.

Step 3 Mark any container holding used GASOLINE, MOGAS, E85, or AVGAS fuel filters with the words "Hazardous Waste/Used Fuel Filters."

Step 4 Place the filters in containers provided. Containers will be closed except when adding or removing waste.

Step 5 If used fuel filters are accumulated at a SAP, write the fill date on the container lid when the container is full, or sooner as needed call **PPOC HazWaste Pick-Up** to schedule a pick-up of the used fuel filters.

Used fuel filters

GENERAL INFORMATION

On-site accumulation of used fuel filters requires establishment of a Satellite Accumulation Point (SAP) and weekly inspections that must be maintained for 3 years. For information contact **Environmental Division Hazardous Waste.**