

## OIL (USED)

USED OIL includes all the following items: Motor Oil, Diesel Fuel, Transmission Fluid, Brake Fluid, Hydraulic Fluid, Synthetic Oils, Heating Oil, Kerosene, & less than 55 gallons of F24/JP8

### POSSIBLE AREAS OF CONCERN

Used Oil potentially contains traces of metals such as chromium, cadmium and lead. Used oil items have a flash point above 100 degrees F.

### CHARACTERIZATION

Used petroleum-based and synthetic oils are non-hazardous industrial wastes and are collected on the installation for recycling.

### HANDLING PROCEDURES

**Step 1** A POL accumulation point is required for bulk quantities (drums or tanks) greater than or equal to 55 gallons. Contact **Environmental Division Hazardous Waste** to establish a POL accumulation point.

**Step 2** Contact **PPOC Services** to obtain a 55-gallon metal drum and Secondary Containment Unit (SCU)

**Step 3** Ensure drum(s), tank(s) and tank fill lines are marked "Used Oil."

**Step 4** Place Used Oil in the drum. Keep drum and SCU closed except when adding or removing contents. Locking is not required but will ensure SCU remains closed.

**Step 5** Contact **PPOC HazWaste Pick-Up/Used Oil** for pickup.

**NOTE:** SCU must be located in an area accessible by a large Pump truck for easy removal.

**NOTE:** **Do Not mix Used Oil with used antifreeze. If antifreeze is contaminated with Oil, contact PPOC Support to get additional guidance.**

**NOTE:** Drip pans/SCU with oil and water should not be poured in Used Oil container. See Drip Pan guidance (A-27) for disposal suggestions.

**NOTE:** Mark oil carts "Used Oil" and empty them daily. **DO NOT USE OIL CARTS FOR STORAGE.**



Used Oil SCU



Small quantities of Used Oil may be placed in your return locker in a "Used Oil" container for pickup

### GENERAL INFORMATION

No solvents or other hazardous wastes can be mixed with Used Oil. If hazardous waste (brake cleaner, parts/weapons cleaner solvent) has been mixed with the oil, contact **PPOC Services**. Incidental amounts (less than 55 gallons) of fuels such as JP8/F24 and diesel may be combined with the Used Oil. For quantities greater than 55 gallons, see protocol sheet, "Fuel F24/JP8 Large Quantity," page A-33. **DO NOT** place MOGAS or Coleman Fuel in the Used Oil container. These items must be transported in a government vehicle to the PPOC for disposal.