

FUEL (F-24/JP8 RECYCLABLE) (Tank Provided by PPOC Services)

POSSIBLE AREAS OF CONCERN

F-24/JP8 is a DOT flammable material and should be handled in accordance with appropriate safety guidelines.

CHARACTERIZATION

Recycled F-24/JP8 can reduce waste of fuel and funds while protecting the environment.

HANDLING PROCEDURES

- Step 1** Selected units have been assigned Recyclable F-24/JP8 containers.
- Step 2** During maintenance operations of fueling vehicles, if drained fuel is good, capture and place in the Recyclable F-24/JP8 container.
- Step 3** When gauge reaches between 25-34 inches, contact **PPOC HazWaste Pickup** to have tank emptied.



Recyclable F-24/JP8 Container

NOTE: This is ONLY for F-24/JP8 – no other fuel or oil product.

1. Do not place separator bottom drainage from recirculation operations. (This material should be placed in USED OIL container.)
2. No purged water.

NOTE: Container must be sealed with a lock to prevent addition of other products. Lock must not be cut. Contact **PPOC Services** if the key is misplaced.

GENERAL INFORMATION

For more information on recycling F-24/JP8, contact **PPOC Services**. See protocol sheet A-33 for large quantities of F-24/JP8.