

DRIP PADS / DRIP PANS

Spill Prevention, Control, and Countermeasure Plan and Stormwater Pollution Prevention Plan



Possible areas of concern and characterization

Petroleum, Oils and Lubricants (POL) can potentially contaminate stormwater systems and ground water. Drip pads/pans are placed under leaking vehicles to prevent POL products from contaminating the soil. Drip pads are designed to capture POL products but not rainwater. A strong preventive maintenance program should be in place at each motor pool which addresses inspecting all vehicles and equipment at the motor pool for conditions that could lead to leaks or spills of hazardous or POL materials. As part of the preventive maintenance program, fluid leaks and/or drips should be reported and scheduled for repairs immediately.

HANDLING PROCEDURES

- Step 1** Place drip pads/pans under leaking vehicles only.
- Step 2** Notify your maintenance section to have the vehicle repaired.
- Step 3** Drip pads/pans must be checked routinely and after each rain fall event.

NOTES

- Fort Knox does not require drip pans to be used unless:
 - You have a leaking vehicle (vehicle should be repaired immediately).
 - You are conducting refueling operations.
 - Your Command SOP dictates the use of drip pans
- Using drip pans creates the potential for spilling oil on the ground or in the storm drains, or not having the proper collection area for collecting or treating the oily water from the drip pans. Drip pads are the preferred method instead of using drip pans for preventing spills.
- Remove POL/sheen from drip pan with oil absorbent. Run any oil water mixture through oil water filter/seperator. Double-bag used absorbent/pads and dispose of at C/DD landfill in contaminated soil roll-off.
- Drip pads that can no longer be used must be double-bagged and disposed of at the C/DD landfill in the contaminated soil roll-off.

CONTACT INFORMATION

502-624-8187/6598