



Final
Site Construction Report
Remedial Action
For the Corrective Action at
Underground Storage Tanks 257-261
Facility Identification Number #9-089118,
Building 430
Fort Stewart, Georgia

CONTRACT NO. DACA21-00-D-0001
Delivery Order No.0008

Submitted to:




Savannah District
ATTN: CESAS-PM-H
100 W. Oglethorpe Avenue
Savannah, Georgia 31401-3640

Submitted by:



J.J. Sosa & Associates, Inc.
5811 Memorial Hwy., Suite 207
Tampa, Florida 33615-5000
(813) 888-6525
(813) 881-1285 (Fax)
Project Number 01-082A
August 2003


Fred G. Portofino, P.G.
Technical Manager

)

)

)

List of Acronyms

°F	Degrees Fahrenheit
AAFES	Army and Airforce Exchange Service
ACE	Anderson Columbia Environmental, Inc.
ACLs	Alternative Cleanup Levels
AS	Air Sparging
BGS	Below Ground Surface
BTEX	Benzene, Toluene, Ethylbenzene, and Total Xylenes
CAP	Corrective Action Plan
COC	Contaminants of Concern
DPW	Fort Stewart Directorate of Public Works
EPA	Environmental Protection Agency
FPM	Feet Per Minute
FSP	Field Sampling Plan
GA EPD	Georgia Environmental Protection Division
ISC	Initial Site Characterization
JJSA	J. J. Sosa and Associates
PSI	Pounds per Square Inch
PVC	Polyvinyl Chloride
RPM	Revolutions per Minute
SAIC	Science Applications International Corporation, Inc.
SCFM	Standard Cubic Feet per Minute
SVE	Soil Vapor Extraction
USACE	U. S. Army Corps of Engineers
VOA	Volatile Organic Aromatics

Table of Contents

1.0	Introduction.....	1
2.0	Site History (Contamination Assessment, Corrective Action Plan, and Remedial Feasibility Testing).....	1
2.1	Soil Vapor Extraction Design	2
2.1.1	Soil Vapor Extraction Wells Installation	3
2.2	Air Sparge Remedial Design	3
2.2.1	Air Sparging Wells Installation	4
2.2.2	Air Sparging Wells Development.....	4
2.3	Groundwater Extraction Well Design.....	5
2.3.1	Groundwater Extraction Wells Installation	5
2.3.2	Groundwater Extraction Wells Development.....	7
2.4	Soil Cuttings Management.....	7
2.5	Subsurface Piping Installation	7
2.6	Remedial Treatment Compound Installation	9
2.6.1	Remedial Equipment Pad Installation and Well Abandonment	9
2.6.2	Electrical Service Installation	9
2.7	Remedial System Installation	10
2.7.1	Groundwater Treatment System	11
2.7.2	Air Sparge Treatment System.....	12
2.7.3	Soil Vapor Extraction Treatment System	12
2.7.4	Groundwater Extraction Pump Installation	12
2.7.5	Security Fence Installation.....	13
2.8	Reinfiltration Gallery Installation.....	13
2.9	Former System Piping Removal and Disposal	14
2.10	Petroleum Contaminated Soils Removal and Disposal	15
2.11	Site Grading and Resurfacing	15
2.12	Discharge Permitting	15
3.0	Conclusions.....	15
4.0	References.....	16

List of Figures

Figure 1	Site Location Map
Figure 2	Soil Vapor Extraction Well Installation Locations
Figure 3	Soil Vapor Extraction Well Vault Construction Detail
Figure 4	Air Sparging Well Installation Locations
Figure 5	Air Sparge Wells Vault Construction Details
Figure 6	Proposed Extraction Wells Capture Zones
Figure 7	Extraction Wells Vault Construction Details
Figure 8	System Piping Locations
Figure 9	Reinfiltration Gallery Installation Location
Figure 10	Pipeline Removal Locations

List of Tables

Table 1	Air Sparging, Soil Vapor Extraction, and Groundwater Extraction Wells Construction Information...
----------------	---

List of Appendices

Appendix A	Soil Boring Logs and Well Construction Diagrams (Field Data)
Appendix B	Well Development Forms Information (Field Data)
Appendix C	Remedial System "As-Built" Drawings
Appendix D	Underground Injection Control Permit #156 Issued by the GA DNR Dated August 29, 2002.

Final
Site Construction Report

1.0 Introduction

J.J. Sosa and Associates, Inc. (JJSA) have been tasked by the United States Army Corps of Engineers (USACE), Savannah District to install, operate, and optimize a groundwater and soil quality remediation system at the location of former Underground Storage Tanks (USTs) 257-261 located near Building 430 at Fort Stewart, Georgia. Remedial action efforts have been employed onsite to mitigate groundwater and soil quality contamination at the site related to historical petroleum releases on the site. The Georgia Environmental Protection Division (GA EPD) facility identification number for the site is #9-089118. The site is located at the Army and Airforce Exchange Service (AAFES) Car Care Center located on Hero Road at Fort Stewart, Georgia (Figure 1).

2.0 Site History (Contamination Assessment, Corrective Action Plan, and Remedial Feasibility Testing)

According to operational information provided by the Fort Stewart Directorate of Public Works (DPW), former UST's 257, UST 258, UST 259, and UST 260 each had a capacity of 10,000 gallons and were used to store gasoline for onsite commercial dispensing purposes. The former tanks were constructed of asphalt coated steel or bare steel, and the associated piping consisted of galvanized steel. The former USTs were installed on or about January 1, 1982 and were removed from the site during March 1993. UST 261 was located next to Building 430 and had a capacity of 500 gallons. Former UST 261 was used to store waste oil generated on the site. UST 261 was constructed of asphalt coated steel or bare steel and the associated piping consisted of galvanized steel. This tank was installed during January 1982 and was removed during June 1996.

Initial Site Characterization (ISC) assessments were conducted by Anderson Columbia Environmental, Inc. (ACE) during the removal of the former UST systems during March 1996 (USTs 257-260) and June 1996 (UST 261). Results of the ISC denoted petroleum contamination near the former tank systems in excess of state petroleum cleanup standards.

Following the completion of the ISC investigations, Science Applications International Corporation, Inc. (SAIC) was retained to conduct a Corrective Action Plan (CAP)-Part A Investigation of the site. The CAP-Part A reports for USTs 257-260 and UST 261 were submitted to the GA EPD UST Management Program during March 1999. Based upon the results of the ISC and the CAP-Part A investigations, a CAP-Part B investigation was determined to be necessary to define and characterize the extent of petroleum contaminated groundwater and soil and to collect additional geologic and hydrologic information to characterize the subsurface site conditions.

The CAP-Part B site investigation was conducted by SAIC during late 1999. The results of the CAP-Part B investigation recommended that active remediation be conducted at the site to restore local soil and groundwater quality conditions. In addition to the aforementioned remedial approach, removal of the remnant fuel system piping associated with USTs 257-260 was also recommended to eliminate any additional sources of continued contamination during construction of the remedial system. The corrective action plan recommended a combination of soil vapor extraction (SVE), air sparging (AS) and groundwater extraction to mitigate site soil and groundwater contamination related with releases from the former UST systems.

After regulatory approval of the remedial approach presented within the CAP-Part B investigation, SAIC prepared an addendum to the workplan entitled "Addendum 13 to Work Plan for Preliminary Groundwater and Corrective Action Plan-Part A/Part B Investigations at Former Underground Storage Tank Sites, Fort Stewart, Georgia" dated December 2001. Site efforts presented as part of the addendum report were used as the basis to conduct site-specific pilot tests for the design of the recommended groundwater pump and treat system, the air sparge system, the vapor extraction system and the combined soil vapor extraction and air sparging systems remedial components. Pilot test activities were conducted during January 2002. In addition to the aforementioned pilot tests, a percolation test was also conducted to provide design information for the placement of a reinfiltration gallery north of the site during remedial construction efforts.

Data generated during the pilot test efforts were used as the basis for the design of the existing remedial system currently operating at the site. Site-specific remedial design information compiled during the pilot tests and the percolation test are presented within the June 2002 report prepared by SAIC and JJSA entitled "Field Sampling Plan for the Corrective Action at Underground Storage Tanks 257-261, Facility Identification Number #9-089118, Building 430, Fort Stewart, Georgia".

2.1 Soil Vapor Extraction Design

Upon review of the remedial design information presented within the June 2002, Field Sampling Plan (FSP) document, three (3) soil vapor extraction (SVE) wells were recommended for installation to remediate residual soil quality contamination. Each soil vapor extraction well was proposed to be constructed of fifteen feet, two inch diameter, schedule 40 polyvinyl chloride (PVC) blank riser and attached to a twelve foot section of well screen. The proposed placement of the soil vapor extraction wells is presented on Figure 2.

Based upon the results of the pilot test investigation, the estimated flow rate designed for each soil vapor extraction well was estimated to be 60 standard cubic feet per minute (scfm). Flow from each of the soil vapor extraction wells is routed to the remedial treatment facility located north-northwest of the existing fuel canopy at the site. Given a design flow of 60 scfm from the three vapor extraction wells, the remedial system equipment purchased for the remedial effort was selected to provide a vacuum induced flow in excess of 180 scfm.

2.1.1 Soil Vapor Extraction Wells Installation

Soil vapor extraction wells 76-SV-1, 76-SV2, and 76-SV3 were installed June 21, 23, and 25, 2002, by Miller Drilling, Inc (Table 1). The borehole advanced at each soil vapor extraction well location measured 8.25-inches in diameter. Each well was installed to a depth from 14.8 to 15.2 feet below existing ground surface using standard hollow stem drilling techniques. Each soil vapor extraction well is equipped with a two-inch diameter twelve-foot long section of schedule 40 PVC well screen. The slot size installed at soil vapor extraction wells 76-SV1, 76-SV2, and 76-SV3 consisted of 0.10-inch factory cut slots. The remaining well construction consisted of 2.0-inch diameter schedule 40 blank PVC riser. Well construction diagrams provided by an SAIC field geologist are presented in Appendix A. Soil boring log data collected during the installation of each vapor extraction well is also presented in Appendix A.

At grade, soil vapor well 76-SV1 was completed within a 19-inch by 19-inch diamond plated well vault equipped with a specialized hex keyed lock. Soil vapor wells 76-SV2 and 76-SV3 were installed within a 29-inch by 30-inch diamond plated well vaults equipped with hex keyed locks. Each well vault installed at the referenced soil vapor well locations is equipped with a 14-inch to 29-inch steel plate constructed subsurface apron set in a concrete pad which extends approximately one foot from the edge of each well vault. Each concrete pad was constructed using 3,000-psi concrete.

The annular space around each soil vapor extraction well was filled with DSI#2 (40/30) sand pack materials. Above the sand pack, 0.6 to 0.5 feet of high yield bentonite slurry was placed with the borehole annulus to seal the wells to the local formation. Above the bentonite seal, the remaining borehole annulus was filled with Portland Type I Cement and bentonite slurry to the bottom invert of the surface protector vault.

After installation, each soil vapor extraction well was connected to a 2.0-inch diameter schedule 40 PVC tee capped with a schedule 40 PVC threaded plug. The port exiting the tee was connected to a segment of 2.0-inch diameter schedule 40 PVC blank tubing connected to a schedule 40 PVC gate valve. After the gate valve, each well was connected to 2.0-inch blank PVC, which was routed through a flanged port cut into the side of each well vault apron. Soil vapor system piping routed from each well vault was buried approximately 1.0-feet deep from each well vault to the remedial treatment compound. Section 2.4 of this report presents the site construction details related with the installation of the buried remedial system piping. Figure 3 presents the detail of the remedial system wellhead piping and the well vault construction details related with the soil vapor extraction wells installed at the AAFES Car Care Center Facility.

2.2 Air Sparge Remedial Design

Data compiled during the pilot tests investigation was evaluated as part of the FSP to yield a design that required the placement of twelve air sparging wells on the site at distinct locations (Figure 4). Upon review of the FSP, each air sparge well was proposed to be installed to a depth from 30 to 35 feet below grade to provide oxygen to the upper portions of the surficial aquifer, locally. The radial influence induced by each air sparge well was calculated to be approximately 25-feet at a maximum pressure of 11.5 pounds

per square inch (psi). Figure 4 presents the locations of the air sparge wells based upon the remedial design presented within the FSP.

2.2.1 Air Sparging Wells Installation

Air sparge wells 76-AS1 through 76-AS12 were installed on June 19, 20, 21, 22, and 24, 2002, by Miller Drilling, Inc (Table 1). The borehole advanced at each air sparge well location measured 8.25-inches in diameter. Each well was installed to a depth from 35.4 to 34.2 feet below existing ground surface using standard hollow stem drilling techniques. Each air sparging well is equipped with a two-inch diameter five-foot long section of schedule 40 PVC well screen. The slot size installed at each air sparge well location consisted of 0.10-inch factory cut slots. The remaining well construction consisted of 2.0-inch diameter schedule 40 blank PVC riser. Air sparging well construction diagrams provided by an SAIC field geologist are presented in Appendix A along with soil boring data collected at each air sparging well location.

At grade, air sparge wells 76-AS-1, 76-AS-2, 76-AS4, 76-AS5, 76-AS6, 76-AS8, 76-AS9, 76-AS10, 76-AS-11, and 76-AS12 have been completed within an 19-inch by 19-inch diamond plated well vault. Air sparging wells 76-AS8 and 76-AS7 were installed within 29-inch by 30-inch diamond plated well vaults. Each well vault is equipped with a lock that can only be opened with a specialized hex head key. Vaults installed at the referenced air sparge wells locations are equipped with a 14-inch to 29-inch steel plate constructed subsurface apron set within a 3,000-psi concrete pad.

The annular space around each air sparge well is filled with DSI#2 (40/30) sand pack materials. Above the sand pack, 2.0 to 5.0 feet of high yield bentonite slurry was placed with the borehole annulus to seal the air sparge wells to the local formation. Above the bentonite seal, the remaining borehole annulus was filled with Portland Type I Cement and bentonite slurry to the bottom invert of the surface protector vault box.

After installation, each air sparge well was connected to a 2.0-inch diameter schedule 40 PVC tee capped with a schedule 40 PVC tapped threaded flush plug. An oil-filled vacuum gauge is attached to each threaded tap plug to monitor vacuum influence at each air sparge well location. The port exiting the tee is connected to a 1.0-inch to 2.0-inch PVC swage/reducer fitting. After the reducer fitting, a segment of 1.0-inch schedule 40 PVC blank tubing is connected to a schedule 40 PVC gate valve. After the gate valve, each well is connected to 1.0-inch schedule 40 blank PVC that is routed through a flanged port cut into the side of each well vault apron. Air sparge system piping routed from each well vault is buried approximately 1.0-foot deep from each well vault to the remedial treatment compound. Section 2.5 of this report presents the site construction details related with the installation of the buried remedial system piping. Figure 5 presents the detail of the remedial system wellhead piping and the well vault construction details related with the air sparge wells installed at the AAFES Car Care Center Facility.

2.2.2 Air Sparging Wells Development

After installation of each of the air sparging wells, SAIC and JJSA field technicians conducted well development to remove residual sediments and clastics from the

emplaced sand packs and hydraulically connect the well screened sections to the local formation. Well development efforts were conducted during June 23 (76-AS5, 76-AS6), June 24 (76-AS4, 76-AS12), June 26 (76-AS1, 76-AS2, 76-AS10, 76-AS11), June 28 (76-AS7, 76-AS9), and June 29 (76-AS3, 76-AS8), 2002. Each soil vapor extraction well was developed with an electrical downhole centrifugal pump followed by surging with a 1.75-inch diameter surge block. Well purge water generated during well development efforts was containerized onsite within a trailer mounted polypropylene tank provided by SAIC. After the tank was filled, the recovered purge water was transported to the on-base decontamination and equipment storage area and treated through virgin activated carbon prior to discharge to the sanitary sewer. Well development information provided by the SAIC field technician is presented in Appendix B. During development of the air sparge wells, a total volume of approximately 1,560 gallons of purge water was generated for disposal.

2.3 Groundwater Extraction Well Design

In addition to the placement of the soil vapor extraction wells and the air sparge wells, pilot test data compiled as part of the FSP recommended the placement of five groundwater recovery wells on the site at discrete locations. The rationale for placement of the groundwater extraction wells was predicated on inducing drawdown within the upper surficial aquifer to control further migration of the contaminant plume to downgradient locations.

Based upon the results from the pilot tests, flow from each proposed groundwater extraction well was estimated at 2.5 gallons per minute in order to maintain a drawdown to negate further contaminant plume migration. Figure 6 presents the proposed capture zones inducted by pumping of the groundwater extractions wells at a flow rate of 2.5 gallons per minute given the evaluation completed within the FSP. Given the combined flow rate of 2.5 gallons per minute, a total liquid flow rate to the remedial system was calculated to be 12.5 gallons per minute. This data was used to size and select the groundwater treatment system purchased for the site. The primary water treatment remedial system component selected for the system was a Nepcco Model HT-363 Turbo Tray Low Profile air stripper.

Upon review of section 3.3.3.3 of the FSP, two groundwater extraction wells (76-EX-4 and 76-EX-5) were installed at the eastern edge of the groundwater contaminant plumes to capture the leading edges of the plumes. Extraction wells 76-EX-1, 76-EX-2, and 76-EX-3 were installed within the groundwater contaminant plume boundaries to control contaminated groundwater migration from the source locations.

2.3.1 Groundwater Extraction Wells Installation

Each groundwater extraction well installed during remedial site construction activities was advanced to depths ranging from 49.2 to 54.5 feet below ground surface (bgs). Extraction well 76-EX1 installed as part of the remedial feasibility tests during January 2002 was converted into a groundwater extraction well and incorporated into the remedial design. Extraction well 76-EX1 was installed on January 17, 2002 by Miller

Drilling, Inc. Extraction wells 76-EX-2, 76-EX3, 76-EX-4, and 76-EX5 were installed by Miller Drilling, Inc. from June 20, 2002 through June 24, 2002 (Table 1).

Each groundwater extraction well was installed to a depth ranging from 45.8 to 50.0 feet bgs using standard hollow stem drilling techniques. The borehole advanced at each groundwater extraction well location measured 12.25-inches in diameter. With the exception of well 76-EX1, each groundwater extraction well is equipped with a 4.0-inch diameter five-foot section of schedule 40 PVC well screen. Extraction well 76-EX1 is equipped with a 30-foot section of slotted well screen. The slot size installed at each extraction well location consisted of 0.10-inch factory cut slots. The remaining well construction consisted of 4.0-inch diameter schedule 40 blank PVC riser. Extraction well construction diagrams provided by an SAIC field geologist are presented in Appendix A along with soil boring log data collected during well installation activities.

At ground surface, extraction wells 76-EX1 and 76-EX2 are completed within a 19-inch by 19-inch diamond plated well vaults equipped with a specialized hex keyed lock. Extraction wells 76-EX 3, 76-EX4, and 76-EX5 are installed within a 29-inch by 30-inch diamond plated well vaults equipped with a hex keyed lock. Each well vault installed at the referenced groundwater extraction well locations are equipped with a 14-inch to 29-inch steel plate constructed subsurface apron set in a concrete pad within extends approximately one foot from the edge of each well vault. Each concrete pad was constructed using 3,000-psi concrete.

The annular space around each groundwater extraction well was filled with DSI#2 (40/30) sand pack materials. Above the sand pack, 2.2 to 0.5 feet of high yield bentonite slurry was placed with the borehole annulus to seal the wells to the local formation. Above the bentonite seal, the remaining borehole annulus was filled with Portland Type I Cement and bentonite slurry to the bottom invert of the surface protector vault.

After installation, each groundwater extraction well was connected to a schedule 40 PVC collar capped with a liquid tight neoprene access port. Electrical lines, pump support cables, and groundwater recovery tubing is routed through the liquid tight well cap within each of the vault locations. Pump support cables are attached to a stainless steel clevis mounted on the sidewall of each vault. Installation of the pump support cable and the clevis at each extraction well location was conducted to adequately support or hang the groundwater extraction pumps within each extraction well allowing for elevational adjustment during remedial operation. Fifty feet of 1.0-inch diameter petroleum resistant rubber tubing connected to each groundwater depression pump is attached to a camlock fitting mounted on the side of each well vault. The camlock fittings are connected to 1.0-inch diameter PVC piping routed from the vaults to the remedial treatment compound. Electrical leads from each on the groundwater depression pumps are connected to liquid tight switches mounted within each vault location.

Section 2.5 of this report presents the site construction details related with the installation of the buried remedial system piping. Figure 7 presents the detail of the remedial system

wellhead piping and the well vault construction details related to the groundwater extraction wells installed at the AAFES Car Care Center Facility.

2.3.2 Groundwater Extraction Wells Development

After installation of each of the groundwater extraction wells, SAIC and JJSA field technicians conducted well development to remove residual sediments and clastics from the emplaced sand pack and hydraulically connect the well screened sections to the local formation. Well development efforts were conducted on July 26, 2002 (76-EX1) and July 28 through July 30, 2002 (76-EX2, 76-EX3, 76-EX4 and 76-EX5).

Each groundwater extraction well was developed with an electrical downhole centrifugal pump followed by surging with a 3.75-inch diameter surge block. Well purge water generated during well development efforts was containerized onsite within a trailer mounted polypropylene tank provided by SAIC. After the tank was filled, the recovered purge water was transported to the on-base decontamination and equipment storage area and treated through virgin activated carbon prior to discharge to the sanitary sewer. Well development information provided by the SAIC field technician is presented in Appendix B. During development of the extraction wells, a total volume of approximately 1,665 gallons of purge water was generated for disposal.

2.4 Soil Cuttings Management

During well installation, all generated soil cuttings were containerized onsite within 55-gallon drums. After the completion of each day of drilling effort, all drums were transported to the on-base decontamination and equipment storage area and secured within a locked fenced compound. A total of 27 drums of waste soil cuttings were generated during the course of the construction activities for the remedial action as a result of well installation efforts.

All drummed soil cuttings were disposed of by Waste Management, Inc as a special waste after the completion of well installation efforts. Final manifests and transportation bill of lading information was transferred to the DPW by SAIC.

2.5 Subsurface Piping Installation

After the completion of the well installation efforts, JJSA and SAIC commenced with the installation of the subsurface piping network associated with the remedial system. Remedial system piping was installed June 26, 2002 through July 25, 2002. All system piping installed at the site was placed within shallow trenches and installed with a rubber-tired backhoe. Prior to installation and excavation of the trenches, the layout of the remedial system piping was located and drawn on the existing pavements and a gas powered concrete/asphalt cutting machine was used to cut and score the existing asphalt and concrete pavements. All surface pavements within the required excavation areas were removed with the backhoe bucket and placed within roll-off dumpsters provided by Waste Management, Inc. for offsite disposal as construction/demolition debris.

Piping installed as part of the soil vapor extraction system was routed from each well vault location to common utilities trench located northeast of the existing canopy. Piping

installed within the common system utilities trench was routed to the treatment compound located northwest of the canopy. Piping installed for air sparge well 76-AS2 was installed southwest of the canopy. Figure 8 presents the locations of the soil vapor extraction piping installed at the site relative to the existing structures and well locations.

All soil vapor extraction piping installed within the trenches consisted of 2.0-inch diameter PVC. Sections of PVC tubing were labeled during installation and connected using glued schedule 40 PVC couplings. Each soil vapor extraction well was equipped with separate piping/conduit directly to the remedial system compound. No manifolds were installed to group these wells. All system piping was buried between depths of one to one and one half feet below existing grade.

Piping associated with the installation of the air sparge wells consisted of 1.0-inch diameter schedule 40 PVC routed from each well installation vault to the common utilities trench. At the common utilities trench, the 1.0-inch diameter pipes were connected to 2.0-inch diameter schedule 40 PVC piping manifolded into a network of individual air sparge well locations. Three segments (Line 1, Line 2 and Line 3) of 2.0-inch diameter PVC air sparging system piping were routed from the common utilities trench to the remedial system compound. Sections of PVC tubing installed as part of the air sparge system were labeled during installation and connected using glued schedule 40 PVC couplings. All system piping was buried between depths of one to one and one half feet below existing grade.

Air sparge wells 76-AS1, 76-AS3, 76-AS8 and 76-AS9 were connected to soil vapor extraction line number 1; air sparge wells 76-AS4, 76-AS5, 76-AS6, and 76-AS7 were connected to soil vapor extraction line number 2; and air sparge wells 76-AS2, 76-AS10, 76-AS11, and 76-AS12 were connected to soil vapor extraction line number 3. Figure 8 presents the locations of the air sparge system piping installed at the site relative to the existing structures and well locations.

Piping associated with the installation of the groundwater extraction wells consists of 1.0-inch diameter schedule 40 PVC routed from each well vault to the common utilities trench. Piping associated with each well was routed through the common utilities trench directly to the remedial system compound. Sections of PVC tubing installed as part of the groundwater extraction system were labeled during installation and connected using glued schedule 40 PVC couplings. All system piping was buried between depths of one to one and one half feet below existing grade. Figure 8 presents the locations of the groundwater extraction system piping installed at the site relative to the existing structures and well locations.

After the completion of remedial system piping installation, all trenches were filled within fine sand fill materials and compacted to approximately three inches below grade. Fill materials were placed within the trenches in six-inch loose lifts and compacted using a mobile plate compactor. After the completion of backfilling efforts, all trench locations were capped with new asphalt.

2.6 Remedial Treatment Compound Installation

The following subsections present the details related with the installation of the remedial system compound currently employed onsite to remediate groundwater and soil quality conditions.

2.6.1 Remedial Equipment Pad Installation and Well Abandonment

During installation of the wells, JJSA field personnel commenced with the installation of the remedial system equipment pad. Equipment pad installation efforts commenced on June 19, 2002 and were completed on June 23, 2002. Installation of the equipment pad was completed in three phases consisting of forming, footers construction, and final concrete pad finishing.

The initial phase of the pad construction efforts consisted of the installation of the forms and minor site grading efforts. Prior to the installation of the forms, Miller Drilling under the supervision of an SAIC geologist abandoned existing shallow well MW 76-30 since this well was located under the proposed pad location. Well abandonment efforts were conducted on June 19, 2002, by filling the well with 3/8-inch chipped bentonite. After the placement of the bentonite, JJSA physically removed the protective well casing with the backhoe bucket.

After the completion of well abandonment efforts, 3/4 inch thick plywood forms were installed around the perimeter of the equipment pad location. After installation of the forms, JJSA field personnel placed #4 rebar within the footers and constructed a rebar-enforced beam that was placed midway between the northeastern and southeastern edges of the pad layout. After placement of the rebar and the forms, JJSA retained Mobile Concrete of Hinesville, Georgia to deliver and pour concrete into the forms to complete the installation of the footers and structural beam construction. After a period of 48 hours, the space between the footers and the central support beam were filled with imported sandy fill materials and compacted in place. After the completion of backfilling and compaction efforts, Mobile Concrete was again contacted to deliver additional concrete to the site to complete the installation of the upper 6-inch section of the equipment pad. Prior to pouring the upper section of the pad, JJSA installed a 4.0-inch by 4.0-inch wire mesh underlayment beneath the upper portion of the pad for additional structural support. All concrete used for the installation of the equipment pad consisted of 3,000-psi fiber-enriched concrete. After placement and curing of the pad, the upper surface was brush finished to provide a skid resistant surface and all structural forms were removed. The final remedial equipment pad measures 22-feet long by 16-feet wide.

2.6.2 Electrical Service Installation

During installation of the remedial equipment during June and July 2002, electrical three-phase electrical service was installed near the southwest corner of the equipment compound area. Electrical service to the remedial equipment was connected to a nearby utility pole located northwest of the equipment compound across 5th Street northwest of the site. Overhead electrical lines and service were connected to a power pole installed by JJSA's electrical contactor, ProLectric, Inc. All power lines routed from the newly

installed pole to the remedial system master power control box were subsequently buried by JJSA after the completion of remedial system installation.

The main remedial system control box mounted on the exterior of the shed consists of a NEMA 4 weather tight enclosure. All of the remedial system controls, switches, and timers are located within the enclosure. System controls are connected to an EOS Procontrol II remote control system that is equipped with a remote telemetry interface and a computer modem. The telemetry system was installed to allow for remote monitoring of the remedial system operations.

In addition to the installation of electric service to the remedial equipment compound, subsurface conduit was also installed within the shallow remedial system piping installation trenches from the treatment shed to each of the groundwater extraction wells. Piping installed consisted of 1.0-diameter PVC Schedule 40 electrical conduit equipped with PVC street elbows to allow for electrical wire installation. During placement of the piping SAIC and JJSA pulled 14 gauge insulated wire through the pipes which was subsequently connected to the system control panel and each groundwater extraction pump. All lines were tested by JJSA personnel prior to the commencement of trench backfilling efforts.

2.7 Remedial System Installation

Soil vapor extraction, air sparging, and groundwater pump and treat remedial equipment were supplied and designed by Nepcco Systems, Inc. (Nepcco) of Ocala, Florida. All remedial equipment components were assembled at Nepcco's remedial assembly facility located at 2140 N.E. 36th Avenue in Ocala, Florida location prior to delivery to the AAFES Car Care Facility. Prior to delivery, JJSA's principal design engineer inspected the system to assure that system construction was in compliance with the operational requirements for the remedial action. Based upon the approved design, JJSA arranged for and accepted delivery of the remedial system to the site on July 24, 2002. Upon arrival of the equipment to the site, JJSA immediately commenced with final installation of the soil vapor extraction piping, air sparge piping, and groundwater extraction piping to the system.

The major remedial system components installed at the site consist of the following:

- (1) Nepcco Model HT-363 Low Profile Air Stripper
- (1) Nepcco Model AWS-115 Air Water Separator
- (2) Rotron Regenerative Blowers Model EN-808BA72MXL
- (1) Roots Model URAI-42 Positive Rotary Blower
- (1) American Fan Model AF-15-1105 Blower
- (5) Master Meter Totalizing Flow Meters (3/4" by 3/4" model)
- (1) Master Meter Flow Transmitter
- (2) Solberg Model FS-31P-200 Filter Silencers
- (2) Myers Model CT-10FAB Water Transfer Pumps
- (2) Dwyer Magnahelic Pressure Differential Indicator Gauge
- (2) Solberg Model CSL-235P-300 Particulate Filters

)

)

)

- (1) Solberg Model FS-18P-150 Particulate Filter
- (3) Micron Tech Model H802EB150CS2B520 Particulate Filter
- (7) Pressure indicators
- (1) Dwyer Model 1004E-A1-J Pressure Switch
- (1) Dwyer Model 1910-1 Pressure Switch
- (2) Stoddard Model PD13-2 Silencers
- (1) Grainger Model 6F60 Silencer
- (4) 55-Gallon Drum Size Liquid Phase Activated Carbon Vessels
- (3) Dwyer Model 0-250F Temperature Indicators
- (1) Dwyer Model RRT225OU Temperature Switch
- (1) Dwyer Model 1950-P2 Vacuum Switch
- (1) Colcraft 10' by 20' Steel Constructed Equipment enclosure with Double Doors
- (1) Thermal Sensor Exhaust Fan
- Numerous Hoses and Dwyer Oil Filled Pressure and Vacuum Gauges.

Remedial system "as-built" drawings and electrical engineering data sheets provided by Nepcco are presented in Appendix C. *The remedial system operation and maintenance manual provided by Nepcco is submitted under separate cover to supplement the Final Construction Report.*

2.7.1 Groundwater Treatment System

The primary remedial system treatment component for recovered groundwater consists of a Nepcco Model HT-363 Turbo Tray low-profile air stripper. The Nepcco Model HT-363 Turbo Tray low-profile air stripper installed onsite measures 5 feet, 9-inches tall by 36 inches in diameter. The air stripper is mounted to a steel skid frame within the enclosure and is bolted to the floor. The air stripper consists of four turbo trays and a sump. The air stripper designed and selected for the remedial action is able to sustain treatment of upto 22 gallons per minute of influent water volume at a maximum blower air flow rate of 250 scfm. Each tray is equipped with quick release clips to aid in stripper disassembly for cleaning. The sump of the stripper is also equipped with a three way level alarm probe used to monitor the height of the water within the sump of the unit during operation. During operation, the level of water within the sump activates a discharge pump which routes water from the sump to the activated carbon vessels for final polishing and treatment prior to discharge to the reinfiltration gallery. Normal operation of the stripper occurs between the low and high sensor levels, which turn the effluent transfer pump on and off. Should the sump flood or overfill with water during operation, the sensor is equipped with a high-high level sensor that when activated will shut the entire system down and activate an alarm. The Nepcco Model 363 Turbo Tray air stripper is also equipped with a mist eliminator and a magnahelic gauge to monitor pressure differentials within the unit during operation. Should the pressure differential within the unit exceed a value of 10 psi or fall below a value of 2 psi during operation, the sensor will shut the entire system down and activate an alarm.

Groundwater entering the Turbo Tray air stripper is routed through an influent manifold located within the interior of the remedial system shed. Groundwater extraction lines entering the shed are routed through ball valves and totalizing flow meters so total volume, flow rates and adjustment may be conducted and recorded during system operation. After the manifold, groundwater is routed through a series of bag filters to remove any residual clastic sediment from the waste stream. After passing through the bag filters, water is routed to the Turbo Tray air stripper for primary treatment.

2.7.2 Air Sparge Treatment System

A Roots Model URAI-42 Positive Rotary Blower mounted to the floor of the remedial system shed controls the air sparging system. The motor for the blower consists of a 5-horsepower, 230-volt, three-phase baldor motor and associated belt drive assembly. The air sparge blower measures 4-foot by 6-foot and is rated for a maximum speed of 3,600 rpm, 15 inches of mercury and a temperature of 240°F. Air to the air sparge wells is routed through a galvanized steel manifold used to cool the air stream mounted on the exterior of the building. Air from the manifold is routed to into three PVC pipes connected to the air sparge wells network (Lines 1, 2 and 3). System settings associated with the air sparge system are controlled by a series of steel gate valves installed on each air discharge pipes. Each air sparge pipe is equipped with a pressure gauge to fine tune pressure settings with the valves. No pressure settings above 11.5 psi are permitted during operation of the remedial equipment.

2.7.3 Soil Vapor Extraction Treatment System

The soil vapor extraction unit consists of a knockout tank to separate air and water within the influent vapor flow, a particulate filter to remove fine clastic sediments, and a blower to provide the vacuum influence to drive the remedial process. Vapor phase contaminants recovered from the soil vapor extraction wells are routed to the treatment compound via the soils vapor extraction wells and the shallow piping. Once at the shed, vapors are routed through a PVC manifold equipped with ball valves and vacuum gauges. The ball valves and gauges located at the main SVE manifold are used to make fine adjustments to the soil vapor extraction system during remedial system operation. After passing through the manifold, vapors are routed through the knockout tank, the particulate filter then through the main system blowers prior to discharge to the atmosphere.

If encountered liquid condensate within the knockout tank is routed through the bag filter and the air stripper for treatment.

2.7.4 Groundwater Extraction Pump Installation

In addition to the aforementioned remedial system components, five (5) Grundfos Model 5E8 (½ Horsepower) 240-volt groundwater depression pumps were delivered to the site for installation into the groundwater extraction wells. Each pump is connected to fifty feet of petroleum resistant reinforce rubber hose and associated stainless steel support cable. The groundwater depression pumps were installed in the wells on July 26 and 27, 2002 and Nepcco's remedial field technician completed final electrical connections immediately after the completion of pump placement.

Each pump has been set at a depth of 43 to 45-feet below grade to bracket the screened interval at each extraction well location.

2.7.5 Security Fence Installation

After the completion of the equipment hookup and calibration, JJSA contraction with Nations Fence, Inc. to install a stockade security fence around the remedial treatment compound. Installation of the six to eight foot tall wood stockade fence commenced on August 19, 2002 and was completed on August 20, 2003. Two access gates have been installed within the fence enclosure. The primary access gate is located on the southwest side of the stockade. A secondary gate is located on the southeastern side of the stockade near the edge of the existing canopy. Both gates are locked and only DWP, USACE and JJSA personnel have keys to the locks.

2.8 Reinfiltration Gallery Installation

During installation of the remedial system piping, JJSA installed an effluent reinfiltration gallery northeast of the remedial system compound. Figure 9 presents the location of the reinfiltration gallery and the associated discharge piping exiting the treatment compound. Reinfiltration gallery design information is presented within the Section 4.1.17 of FSP.

Liquid effluent generated by the onsite remedial treatment activities is routed to the reinfiltration gallery via one-inch diameter schedule 40 PVC piping. The PVC piping is installed within a shallow trench running northeast of the treatment compound then northwest Building 430 crossing 5th Street (Figure 9).

As part of the reinfiltration gallery installation, JJSA installed six (6) thirty-foot segments of buried sewer drainpipe within the gallery installation area. Each segment of pipe was connected to a buried dispersion manifold consisting of 4.0-inch diameter schedule 40 PVC. Four-inch schedule 40 PVC elbows and street tees were used to connect the drain piping to the manifold. Trenches excavated during installation of the gallery measured 32 feet in length, 1 foot wide by 2 foot deep. After excavation of the trenches, one foot of washed pea gravel was placed within the trenches after which the drainpipe was installed above the basal gravel layer. After placement of the drainpipe within each trench, 6 to 8 inches of pea gravel was placed above the drainpipe. Fine mesh filter fabric was placed on top the gravel and the excavated soils were thin spread over the gallery installation area.

In addition to the effluent discharge piping, a second one-inch diameter PVC pipe was installed within the gallery discharge trench to provide a conduit for electrical supply lines to energize a high level sensor installed within well 76-GA-01 installed east of the gallery. Well 76-GA-01 was installed to a depth 14.9 feet below grade to monitor water table mounding during gallery operation (Table 1). Well 76-GA-01 is equipped with a ten foot section of 0.10-inch slotted well screen set within a DSI #2 (40/30) sandpack. Above the sandpack, two feet of bentonite was placed within the annular space to seal the well to the native formation. After placement of the bentonite seal, the observation well was grouted to one foot below surface and set within an eight-inch diameter steel flush-

mount well protector. Miller Drilling, Inc. installed well 76-GA-01 on June 24, 2002 under the supervision of an SAIC field geologist. Well installation information and log of boring data provided by SAIC is presented in Appendix A.

The high liquid level float sensor installed within well 76-GA-01 is connected to the remedial system control panel and the EOS Procontrol II panel via 14 gauge wiring installed within 1.0-inch diameter PVC pipe. Should the water table ever trip the sensor due to a high water table condition induced by failure of the gallery, the remedial system will shut down and all flow to the gallery will be terminated immediately.

2.9 Former System Piping Removal and Disposal

During installation of the remedial system piping, JJSA removed all accessible segments of the former fuel distribution piping associated with former USTs 257, 258, 259, 260, and 261. The former system piping was found to be located approximately 4 to 6 feet northeast of the eastern edge of the onsite canopy structure at a depth ranging from three to four feet below grade. The former system piping east of the canopy consisted of three-inch diameter steel piping encased within a yellow epoxy resin coating. The three-inch diameter fuel system piping appeared to be in good to excellent condition.

From the primary trunk piping, two inch diameter bare steel piping was routed to the southwest towards each of the former pump islands under the existing canopy. Concrete above each of these pipes was removed and the dispenser piping at each pump island was physically extracted during remedial construction efforts. Piping removed near the pump islands appeared to be in relatively poor condition and displayed visual evidence of severe corrosion and pitting.

All former fuel distribution system piping removed from the site was drained, cleaned, and disposed of offsite as demolition debris.

Former system piping located in close proximity to wells 76-EX2, 76-AS3, 76-SV1, 76-AS1, and monitoring wells MW-76-21 and MW-76-41 could not be safely removed without potentially damaging the wells. After a meeting with DPW, USACE, SAIC, and JJSA personnel on June 26, 2002, the decision was made to decontaminate the residual system piping encountered near the aforementioned wells in place then, fill the former pipes with pressure grout slurry. As such, approximately 80 linear feet of the former system piping was cleaned with a drum vacuum, sprayed with a high-pressure washer, and grouted in place. Figure 10 presents the locations of the former system piping removed from the facility. Onsite piping decontamination and cleaning effort generated one 55-gallon drum of waste fluids that was labeled and moved to the on-base waste storage location for staging for disposal.

U.S. Liquids of Georgia, Inc disposed of the liquid waste material generated during cleaning of the former fuel distribution system piping.

2.10 Petroleum Contaminated Soils Removal and Disposal

During removal of the former fuel distribution piping and installation of the remedial system piping, petroleum contaminated soils were excavated and placed within lined roll-off dumpsters for offsite disposal. Excavation efforts conducted during removal of the former fuel system product lines were advanced approximately three feet beyond the inverts and sides of the former system piping to effectively remove the soil contamination. The total volume of soil removed from the site for offsite disposal was 191.01 tons. All petroleum-contaminated soil excavated from the site during construction efforts were transported and disposed of offsite at the Superior Landfill & Recycling Center located at 3001 Little Neck Road, Savannah, Georgia.

2.11 Site Grading and Resurfacing

After the completion of the removal of the former system piping, the removal of the former fuel distribution pipelines and the installation of the remedial system piping, JJSA commenced with final site grading and resurfacing efforts. Concrete beneath the islands removed to excavate the former fuel system piping was repoured to match the existing concrete pavements and structures. Trenches cut to install the remedial system piping and/or removed the former fuel distribution piping were cut and resurfaced with three inches of asphalt. The area in and around the reinfiltration gallery was seeded with hybrid grass seed.

2.12 Discharge Permitting

Prior to the commencement of the remedial action, the Georgia Environmental Protection Division granted an Underground Injection Control Permit (UICP) for the facility. A copy of the UICP #156 for injection of treated ground water and ambient air is presented in Appendix D for reference. The UICP sets conditions related with reporting, maximum air and treated groundwater injection volumes, compliance requirements related with discharge standards, and regulatory notification requirements associated with operation of the remedial system. The UICP was received by JJSA on September 9, 2002. Upon receipt of the UICP, all remedial system components were placed within an automatic operational mode and active remedial system operations formally commenced.

3.0 Conclusions

This report presents the site-specific information related with the installation and design of the remedial system at the AAFES Car Care Center located at Building 430, Fort Stewart, Georgia. Detailed information related with the operation of the remedial system and all associated groundwater and air monitoring data compiled during the first six months of remedial system operation are presented within JJSA's supplemental technical report entitled "First Semi-Annual Remedial Monitoring Report" dated August 2003.

4.0 References

J.J. Sosa and SAIC (Science Applications International Corporation), *Corrective Action Plan Part B for the Corrective Action at Underground Storage Tanks 257-261, Facility Identification Number #9-089118, Building 430, Fort Stewart, Georgia*, June 2000.

J.J. Sosa and SAIC (Science Applications International Corporation), *Addendum #13 to Work Plan for Preliminary Groundwater and Correction Action Plan – Part A/Part B Investigations at Former Underground Storage Tanks Sites Fort Stewart, Georgia*, December 2001.

J.J. Sosa and SAIC (Science Applications International Corporation), *Field Sampling Plan for the Corrective Action at Underground Storage Tanks 257-261, Facility Identification Number #9-089118, Building 430, Fort Stewart, Georgia*, June 2002

J.J. Sosa & Associates, Inc., *NEPCCO Groundwater Remediation System for Facility Fort Stewart, Hinesville, Georgia, NEPCCO Job#11291*, July. 2002.

SAIC (Science Applications International Corporation) 1996a. *Work Plan for Preliminary Groundwater and Corrective Action Plan-Part A/Part B Investigations at Former Underground Storage Tanks Sites, Fort Stewart, Georgia*. Oak Ridge, Tennessee, August.

SAIC (Science Applications International Corporation) 1996b. *Site Safety and Health Plan for Preliminary Groundwater and Corrective Action Plan-Part A/Part B Investigations at Former Underground Storage Tanks Sites, Fort Stewart, Georgia*. Oak Ridge, Tennessee, August.



SAIC 1999a. *Corrective Action Plan-Part A for USTs 257-260, Facility ID 9-089037, Building 430, Fort Stewart, Georgia*. Oak Ridge, Tennessee, March.

SAIC 1999b. *Corrective Action Plan-Part A for UST 261, Facility ID 9-089118, Building 430, Fort Stewart, Georgia*, Oak Ridge, Tennessee, March.

SAIC 2000. *Corrective Action Plan – Part B for USTs 257-261, Facility ID 9-089118, Building 430, Fort Stewart, Georgia*. Oak Ridge, Tennessee, January.

USACE, Scope of Work (SOW), Remedial Action at the Former AAFES Gas Station (BLDG 430) Fort Stewart, Georgia, Final September 24, 2001.

Figures




J.J. SOSA & ASSOCIATES, INC.
 5811 MEMORIAL HIGHWAY,
 SUITE 207 TAMPA, FL 33615
 (813) 888-6525 Fax: (813) 881-1285

FIGURE 1 SITE MAP

UST's 257-261, Building 430
 Facility ID # 9-089118
 Fort Stewart, Georgia

FIGURE 1

USACE dwg

Scale:
 1"=1150 ft

Proj. No:
 01-082

PM: FGP

5/21/03

)

)


)

PLOTTED:

Figure
2

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

SOIL VAPOR EXTRACTION
INSTALLATION LOCATION






Figure
3

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

SOIL VAPOR EXTRACTION
VAULT CONSTRUCTION DETAILS

PLOTTED:

)

)

)




Figure
4

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

AIR SPARGE WELL
INSTALLATION LOCATIONS

)

)

)




Figure
5

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

AIR SPARGE WELLS
VAULT CONSTRUCTION DET.

)

)

)




Figure
6

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

PROPOSED EXTRACTION WELL
CAPTURE ZONES




Figure
7

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

EXTRACTION WELLS
VAULT CONSTRUCTION DET.

)

)

)




Figure
8

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

SYSTEM PIPING LOCATIONS

)

)

)




Figure
9

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

REINFILTRATION GALLERY
INSTALLATION LOCATIONS

)

)

)




Figure
10

USTs 257-261, BUILDING 430
FACILITY ID # 9-089118
WELL LOCATIONS
FORT STEWART, GEORGIA

PIPELINE REMOVAL LOCATION

)

()

)

Tables

Table 1
Air Sparging, Soil Vapor Extraction and Groundwater Extraction Wells Construction Information
AAFES Car Care Facility
Building 430
Corrective Action at USTs 257-261
Facility Identification #9-089118
Ft. Stewart, Georgia

Well Designation	Installation Dates	Total Borehole Depth	Borehole Diameter	Bottom of the Screened Interval	Top of Well Screened Interval	Well Screen Length	Top of the Sand Pack	Top of the Bentonite Seal
	Start	Finish	(ft. bgs)	(inches)	(ft. bgs)	(ft.)	(ft. bgs)	(ft. bgs)
Air Sparging Wells								
76-AS1	06/20/02	06/20/02	40.5	8.25	35	5	27.6	23.1
76-AS2	06/24/02	06/24/02	38	10 to 12	35	5	27	19
76-AS3	06/20/02	06/20/02	35	8.25	34.5	5	27	25
76-AS4	06/20/02	06/20/02	35	8.25	34.2	5	27	23
76-AS5	06/20/02	06/21/02	34.7	12.85	29.5	5	27.5	24.2
76-AS6	06/19/02	06/19/02	36	8.25	34.5	5	27.8	26
76-AS7	06/22/02	06/25/02	38	8.25	35	5	28	24.9
76-AS8	06/21/02	06/22/02	37	8.25	34.7	5	27.5	21.9
76-AS9	06/22/02	06/22/03	36	8.25	35.4	5	27.5	25.5
76-AS10	06/20/02	06/20/02	35.5	8.25	34.9	5	27	23
76-AS11	06/19/02	06/19/02	35.5	8.25	35.28	5	28	26
76-AS12	06/20/02	06/20/02	35.5	8.25	34.78	5	25	23
Vapor Extraction Wells								
76-SV1	06/21/02	06/22/02	15.5	8.25	14.88	12	2.5	1.9
76-SV2	06/25/02	06/25/02	16	8.25	15.2	12	2.5	2
76-SV3	06/23/02	06/23/02	15.2	8.25	15	12	2.5	2
Groundwater Extraction Wells								
76-EX1	01/17/02	01/18/02	47	12.25	45.8	30	12.5	8.9
76-EX2	06/24/02	06/24/03	49.2	12.25	49	10	37.2	32.2
76-EX3	06/20/02	06/21/02	51.5	12.25	49.8	10	38.1	35.9
76-EX4	06/22/02	06/25/02	54	12.25	50	10	38	33
76-EX5	06/23/02	06/23/02	54.5	12.25	49	10	36.8	32.3
Infiltration Gallery Observation Well								
76-GA-01	06/24/02	06/24/02	15.5	8.25	14.9	10	3.8	1.9

Appendix A
Soil Boring Logs and Well Construction Diagrams
(Field Data)

TRW DRILLING LOG

DISTRICT USACE - Savannah

HOLE NUMBER

EX-1

1. COMPANY NAME: SAIC

2. DRILL SUBCONTRACTOR:

Miller

SHEET 1 OF 2

3. PROJECT: Fort Stewart

4. LOCATION:

5. NAME OF DRILLER:

S. Gentry

6. MANUFACTURERS DESIGNATION OF DRILL

7. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT

8" Hollow Stem Auger

8. HOLE LOCATION:

CA-401 Center

9. SURFACE ELEVATION:

10. DATE STARTED:

01/17/02

11. DATE COMPLETED:

01/18/02

12. OVERBURDEN THICKNESS

NA

15. DEPTH GROUNDWATER ENCOUNTERED:

13. DEPTH DRILLED INTO ROCK

NA

16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:

14. TOTAL DEPTH OF HOLE

470. BLS

17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):

18. GEOTECHNICAL SAMPLES

DISTURBED

UNDISTURBED

19. TOTAL NUMBER OF CORE BOXES

20. SAMPLES FOR CHEMICAL ANALYSIS

VOC

METALS

OTHER (SPECIFY)

OTHER (SPECIFY)

OTHER (SPECIFY)

21. TOTAL CORE RECOVERY %

22. DISPOSITION OF HOLE

BACKFILLED

MONITORING WELL

OTHER (SPECIFY)

23. SIGNATURE OF INSPECTOR

[Signature]

LOCATION SKETCH/COMMENTS

SCALE:

Grid area for location sketch/comments. Handwritten notes include:

- Plan
- W 14
- 20'
- 14'

HTRW DRILLING LOG

PROJECT: Fort Stewart UST's

INSPECTOR: *W. H. R.*

HOLE NUMBER 76-EV-1

SHEET 2 OF 2

62

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		0.0 - 0.3 gravel 30/37				20 ppm low
		0.3 - 2.2 clayey sand (SC) greenish gray silt medium grained subangular firm				70 ppm low
		2.2 - 3.3 silty sand (SM) light gray mb medium grained subangular moist sett.				500 ppm low
		3.3 - 4.0 silty sand (SM) light gray 10/12 7/2 to black 10/12 2/1 medium grained subangular moist to wet				293 ppm low
		4.0 - 4.7 silty sand (SM) light gray 10/12 7/2 to black 10/12 2/1 medium grained subangular moist to wet				870 ppm low
		4.7 - 7.0 more organics at 7.0 BLS				720 ppm comp 250 ppm low
		Drill cut 70 47.0 BLS				

HTRW DRILLING LOG

OBJECT: Fort Stewart UST's

INSPECTOR

HOLE NUMBER

SHEET OF

63

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

Handwritten: 11/18/62

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008

MONITORING WELL ID: 76-E1

INSTALLATION START: DATE: 01/17/02 TIME: 1345

INSTALLATION FINISH: DATE: 01/18/02 TIME: 1108

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSE #2 QUANTITY: 34 bags
 BENTONITE SEAL: TYPE: 2 uncoated pellets QUANTITY: 4 buckets
 GROUT: TYPE: Portland Cement QUANTITY: 8 bags

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.02 SLOT CONFIGURATION: Slotted Horizontal
 TOTAL OPEN AREA PER FOOT OF SCREEN: _____
 OUTSIDE DIAMETER: 4" NOMINAL INSIDE DIAMETER: _____
 SCHEDULE/THICKNESS: 40 COMPOSITION: _____
 MANUFACTURER: _____

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter pack natural formation

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 4" NOMINAL INSIDE DIAMETER: _____
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER: _____

JOINT DESIGN AND COMPOSITION: Welded with 01/17/02 Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION: N/A

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: N/A COMPOSITION: _____

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

N/A

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES ☒ NO ☐

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐


QUANTITY OF APPROVED WATER USED FOR FILTER PACK EMPLACEMENT: 50 gallons

RECORDED BY: Wendy H. Kim


QA CHECK BY: _____

69

MONITORING WELL		
PROJECT: AAFES Car Care Center, USTs 257-261		DELIVERY ORDER NO: 008
WELL NUMBER: 76-E1	BEGIN: 01/17/02	END: 01/18/02
COORDINATES: N:	REFERENCE POINT: ELEVATION: DATUM/UNIT:	
E:		
DATUM/UNITS:		



TRW DRILLING LOG		DISTRICT: USACE - Savannah		HOLE NUMBER 76-EX2	
COMPANY NAME: SAIC		1. DRILL SUBCONTRACTOR: <i>Miller Drilling</i>		SHEET 1 OF 2	
PROJECT: <i>PAFES Cor-Loc Center</i>		4. LOCATION: <i>500 map Below</i>			
NAME OF DRILLER:		6. MANUFACTURERS DESIGNATION OF DRILL: <i>Mobil B-57</i>			
8. HOLE LOCATION: <i>500 map Below</i>		9. SURFACE ELEVATION:			
10. DATE STARTED: <i>06/24/02</i>		11. DATE COMPLETED: <i>06/24/02</i>			
15. DEPTH GROUNDWATER ENCOUNTERED:		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):					
1. GEOTECHNICAL SAMPLES		DISTURBED		UNDISTURBED	
SAMPLES FOR CHEMICAL ANALYSIS		VOC		OTHER (SPECIFY)	
DISPOSITION OF HOLE		BACKFILLED		OTHER (SPECIFY)	
<i>Extraction Well</i>					



ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	0.0 - 0.3					
	$\frac{3}{5.0}$	spoon #1				
	0.3 - 2.0	clayey sand greenish gray 10% bl. medium to fine grained moist, firm subangular	CORP = 8.0 ppm HS = 435 ppm			
	2.0 - 3.5	silty sand light greenish gray 10% bl. fine grained, subangular moist soft	CORP = 11.0 ppm HS = 2.5 - 5.0 635 ppm			
	spoon #2					
	$\frac{4.0}{5.0}$					
	5.0 - 6.0	WAP 66/24/02				
	4.0 - 5.0	some to above	CORP = 85 ppm			
	6.0 - 9.0	silty sand BLACK M fine grained, subangular, soft moist to saturated	HS = 126 ppm			
			CORP = 105 ppm HS = 200 ppm			
						Water table ± 10.0 BLS

HTRW DRILLING LOG						HOLE NUMBER
ECT:			INSPECTOR		SHEET OF	
DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)	
11						
12						
13						
14						
15						
16						
17						
18						
19						

Wmpt. Par. 6/24/02

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-EX2

INSTALLATION START: DATE: 06/24/02 TIME: 0815

INSTALLATION FINISH: DATE: 06/24/02 TIME: 1800

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK:	TYPE: <u>DSI #2</u>	QUANTITY: <u>650 lbs</u>
BENTONITE SEAL:	TYPE: <u>sure seal</u>	QUANTITY: <u>100 lbs</u>
GROUT:	TYPE: <u>Portland</u>	QUANTITY: <u></u>

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.010 #10 SLOT CONFIGURATION: slotted horizontal

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.35 NOMINAL INSIDE DIAMETER: 0.33

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN:

Filter / Formation pack

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.35 NOMINAL INSIDE DIAMETER: 0.33

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

JOINT DESIGN AND COMPOSITION:

Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION:

NONE

DESCRIPTION OF PROTECTIVE CASING:

NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Formation was heaving into Augers during installation of filter pack and seal

Was all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Was all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical leakage and/or defects? YES ☒ NO ☐

Was deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK REPLACEMENT: 50 gallons

RECORDED BY:

Wanda H. Pina - 06/24/02

QA CHECK BY:

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-EX 2


BEGIN: 06/24/02

END: 06/24/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:


DATUM/UNITS:



1. WELL DRILLING LOG		DISTRICT: USACE - Savannah		HOLE NUMBER 76-ASS/EX 3	
COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: Miller Drilling		SHEET 1 of 3	
PROJECT: AAFES Car Care Center		4. LOCATION: 500 MGP below			
NAME OF DRILLER:		6. MANUFACTURERS DESIGNATION OF DRILL			
TESTS AND TYPES OF DRILLING SAMPLING EQUIPMENT Mod. B-57		8. HOLE LOCATION: 500 MGP below			
8 1/2 (OD) Augers with CME span over drill with 12 1/4 Augers to install MHI		9. SURFACE ELEVATION:			
OVERBURDEN THICKNESS NA		10. DATE STARTED: 06/20/02		11. DATE COMPLETED: 06/21/02	
DEPTH DRILLED INTO ROCK NA		15. DEPTH GROUNDWATER ENCOUNTERED: 2 to BLS			
TOTAL DEPTH OF HOLE 51.5		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
GEOTECHNICAL SAMPLES		DISTURBED		UNDISTURBED	
SAMPLES FOR CHEMICAL ANALYSIS		VOC		OTHER (SPECIFY)	
EXPOSITION OF HOLE		BACKFILLED		MONITORING WELL	
Monitor well				19. TOTAL NUMBER OF CORE BOXES	
				21. TOTAL CORE RECOVERY: NA	
				23. SIGNATURE OF INSPECTOR [Signature]	

ON SKETCH/COMMENTS

SCALE:



34

Wm. H. Purr

SHEET 2 OF 3

Ex 3

76-54252

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76- A55


BEGIN: 06/20/02

END: 06/21/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:

DATUM/UNITS:



MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-EX3

BEGIN:

06/24/02

END:

06/21/02

COORDINATES: N:

E:

REFERENCE POINT:

ELEVATION:

DATUM/UNITS:

DATUM/UNITS:

PR

MOI

INS

INS

ANN

DES

TYP

DES

JOIN

CEN

DES

SPE

Was

etc.)?

Was


break

Is del

retrie

QUAI

RECC



HOLE DIA: (IN)


12 1/4

5

TRW DRILLING LOG		DISTRICT USACE - Savannah		HOLE NUMBER 76-EX4/AS7	
COMPANY NAME: S.I.C.		2. DRILL SUBCONTRACTOR: Miller Drilling		SHEET 1 OF 2	
3. PROJECT: AAFES Corp Care Center			4. LOCATION: See Below		
5. NAME OF DRILLER: Paul Gibson			6. MANUFACTURERS DESIGNATION OF DRILL B-57		
7. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT 8 1/4 OD Auger with CME 500mm to 1 water table with over drilled with 12 1/4			8. HOLE LOCATION: See Below		
12. OVERBURDEN THICKNESS NA			9. SURFACE ELEVATION:		
13. DEPTH DRILLED INTO ROCK NA			10. DATE STARTED: 6/22/02 11. DATE COMPLETED: 6/25/02		
14. TOTAL DEPTH OF HOLE 56.9 / 54.0 / 38.0			15. DEPTH GROUNDWATER ENCOUNTERED:		
16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):		
18. GEOTECHNICAL SAMPLES		DISTURBED		UNDISTURBED	
19. TOTAL NUMBER OF CORE BOXES		20. TOTAL CORE RECOVERY		21. SIGNATURE OF INSPECTOR W. H. P.	
22. DISPOSITION OF HOLE Extraction well		23. SIGNATURE OF INSPECTOR		24. SIGNATURE OF INSPECTOR	

LOCATION SKETCH/COMMENTS

SCALE:



HTRW DRILLING LOG						HOLE NUMBER 76-EX4/457
PROJECT: AAF E Car Care Center			INSPECTOR: W. R. R.			SHEET 2 OF 2
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEO TECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		spoon #1 asphalt 0.0-0.5 φ-5.φ				
		3.9/5.0	corp 153ppm			
		0.5 to 2.0 sand with silt light gray 7/1 104/2	9.8 ppm = HS			
		fine grained to medium grained subangular moist				
		2.0 - 3.5 sand with silt light brownish gray 104/2 5/2	corp 423ppm			
		fine grained subangular, moist poorly graded	HS = 142ppm			
		spoon #2 5.0-10.0 5.0/5.0				
		5.0-5.5 smp as above	corp 75ppm			
		5.5 - 10.0 silly sand ~ 35% silt, black oil fine grained subangular, moist to saturated	2216ppm HS			
			HS = 1054ppm corp 957ppm			
						water table

HTRW DRILLING LOG

HOLE NUMBER

INSPECTOR

SHEET OF

ОБЪЕКТ:

ELEV.
(A)

DEPTH
(31)

DESCRIPTION OF MATERIALS
(G)

HEADSPACE SCREENING RESULTS

GEOTECH
SAMPLE
OR CORE BOX

ANALYTICAL
SAMPLE NO.
(F)

REMARKS
(U)

11

12

13

14

15

16

17.

18

19

06/22/14

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-EX4

INSTALLATION START: DATE: 06/22/02 TIME: 0800

INSTALLATION FINISH: DATE: 06/25/02 TIME: 1430

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 100 lbs
 BENTONITE SEAL: TYPE: High yield Bentonite QUANTITY: 25 gallon slurry
 GROUT: TYPE: Concrete Type I QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.010 #10 SLOT CONFIGURATION: Slotted Horizontal
 TOTAL OPEN AREA PER FOOT OF SCREEN:
 OUTSIDE DIAMETER: 0.35 NOMINAL INSIDE DIAMETER: 0.33
 SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC
 MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter / sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.35 NOMINAL INSIDE DIAMETER: 0.33
 SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC
 MANUFACTURER: DSI

JOINT DESIGN AND COMPOSITION: Flush threaded

CENTRALIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

76-EX4 / AS7 was to be a stacked
pair but because of heavy sands
AS7 was installed in a separate hole

Was all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Was all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical leakage and/or defects? YES ☒ NO ☐

Was deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 100 gallons

RECORDED BY: 11 R

QA CHECK BY: 11 R

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-EX4


BEGIN: 06/22/02

END: 06/25/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:

DATUM/UNITS:



MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS7INSTALLATION START: DATE: 06/22/02 TIME: 0800INSTALLATION FINISH: DATE: 06/25/02 TIME: 1655

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 150 lbsBENTONITE SEAL: TYPE: Sure Seal QUANTITY: 50 lbsGROUT: TYPE: Portland QUANTITY: DESCRIPTION OF WELL SCREEN: Type I/BentoniteSLOT SIZE (inches): 0.020 SLOT CONFIGURATION: Slotted HorizontalTOTAL OPEN AREA PER FOOT OF SCREEN: NAOUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17SCHEDULE/THICKNESS: PVC SCH 40 COMPOSITION: PVCMANUFACTURER: DSITYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter pack/Formation

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVCMANUFACTURER: DSIJOINT DESIGN AND COMPOSITION: Flush ThreadedCENTRALIZERS DESIGN AND COMPOSITION: NONEDESCRIPTION OF PROTECTIVE CASING: NONENOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Was all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Was all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical leakage and/or defects? YES ☒ NO ☐

Was deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: RECORDED BY: [Signature]

(Signature & Date)

QA CHECK BY: [Signature]

(Signature & Date)

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS7


BEGIN: 6/22/02

END: 6/25/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:

DATUM/UNITS:



HTRW DRILLING LOG						HOLE NUMBER
PROJECT: 11573		INSPECTOR JKH				SHEET 1 OF 1
LEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		Asphalt & Gravel				Auger to 3' with sampler
		CLAYEY SAND (SC), 10% clay, medium grained, subangular, firm moist, 10YR-5/6 yellowish brown	9.6 ppm 173.0			
		No Recovery				
		Bottom of hole 3.0'				Hit active water line

SHEET / OF /

INSPECTOR JKH

SHEET / OF /

[illegible]

67

HTRW DRILLING LOG					HOLE NUMBER
T: 13T 257-261			INSPECTOR JKL		7-4-01
DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
1	Asphalt				Offset from first hole ~ 2' and auger to 3' with sampler
1 1/2	CLAYEY SAND (SC), 10% clay, medium grained, sub-angular, firm, moist, Olive Gray 5Y-4/3				
2	SILTY SAND (SM) 30% silt, fine to very fine grained, soft, dry, Dark Brown, 10YR-3/3	> 3000 ppm 1207			
3	No Recovery				
3 1/2	SAND (SP), very fine to fine grained, very soft, dry, Yellow, 10YR-7/6	> 3000 ppm 1213			Auger to 8' with sampler
4	No Recovery				
5					
6					
7					
8					
8 1/2	SILTY SAND (SM) 20% silt, very fine grained, firm, moist, Dusky Red - 10R-3/3	> 3000 1320			Auger to 13' with sampler
9					

HTRW DRILLING LOG						HOLE NUMBER <u>78-41-01</u>
OBJECT: <u>15T 257-261</u>		INSPECTOR <u>JXL</u>				SHEET <u>1</u> OF <u>1</u>
EV. NO.	DEPTH (ft)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (D)	REMARKS (G)
	11	SANDY SILT (ML), 40% very fine sand, soft, moist, Black, 10YR-3/1 Wet at 12.1'	72000 _{11m}		7610131	V
	12		1231			
	13					
	14					Discontinue sampling and auger to 15.5'
	15					
	16	Bottom of hole 15.5'				
	17					
	18					
	19					
	20					
	21					

MONITORING WELL INSTALLATION LOG

SUBJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-51-01

INSTALLATION START: DATE: 6-21-02

TIME: 1700

INSTALLATION FINISH: DATE: 6-22-02

TIME: 1330

MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: #3 sand QUANTITY: 9 50lb bags

BENTONITE SEAL: TYPE: 3/8" bentonite pellets QUANTITY: 1/2 of 5 gal. bucket

GROUT: TYPE: Portland Cement Grout QUANTITY: _____

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.20" SLOT CONFIGURATION: horizontal cut

TOTAL OPEN AREA PER FOOT OF SCREEN: _____

OUTSIDE DIAMETER: 19' NOMINAL INSIDE DIAMETER: 17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: _____

DESCRIPTION OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN:

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 19' NOMINAL INSIDE DIAMETER: 17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: _____

WELL DESIGN AND COMPOSITION: Flush Threaded

STABILIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" square COMPOSITION: Steel Flush Mount

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

leaving sands - flushed down with water

all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,

? YES [☒] NO [☐]

all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical

damage and/or defects? YES [☒] NO [☐]

distortion or bending of the installed well screen and casing minimized to the point of allowing the insertion and

of a 1.0-inch bailer throughout the entire length of the completed well? YES [☒] NO [☐]

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: _____

RECORDED BY: [Signature]
(Signature & Date)

QA CHECK BY: [Signature] 8/1/02
(Signature & Date)

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-56-01


BEGIN: 6-8-02
1700

END: 6-22-02
1330

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS


DATUM/UNITS:



50

W DRILLING LOG		DISTRICT USACE - Savannah	HOLE NUMBER 76-SV2
COMPANY NAME SAIC		2. DRILL SUBCONTRACTOR: <i>Miller Drilling</i>	SHEET <u>1</u> OF <u>2</u>
PROJECT: <i>AAFES Cu Cove Center</i>		4. LOCATION: <i>see map below</i>	
NAME OF DRILLER: <i>P. Gibson</i>		6. MANUFACTURERS DESIGNATION OF DRILL: <i>MOBILE R-57</i>	
SIZES AND TYPES OF DRILLING & SAMPLING EQUIPMENT: <i>8 1/4" Hollow stem Auger and CME 4000</i>		8. HOLE LOCATION: <i>see map below</i>	
		9. SURFACE ELEVATION:	
		10. DATE STARTED: <i>6/6/20/02</i> 11. DATE COMPLETED: <i>6/6/25/02</i>	
OVERBURDEN THICKNESS		15. DEPTH GROUNDWATER ENCOUNTERED:	
DEPTH DRILLED INTO ROCK <i>NA</i>		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:	
TOTAL DEPTH OF HOLE <i>NA</i>		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):	

GEOTECHNICAL SAMPLES	DISTURBED	UNDISTURBED	19. TOTAL NUMBER OF CORE BOXES		
SAMPLES FOR CHEMICAL ANALYSIS	VOC	METALS	OTHER (SPECIFY)	OTHER (SPECIFY)	OTHER (SPECIFY)
	<i>Enter</i>				
DISPOSITION OF HOLE	BACKFILLED	MONITORING WELL	OTHER (SPECIFY)	21. SIGNATURE OF INSPECTOR	
<i>Monitor well</i>	<input checked="" type="checkbox"/>			<i>[Signature]</i>	



51

HTRW DRILLING LOG		HOLE NUMBER 76-542
OBJECT:	INSPECTOR <i>Wagott-R</i>	SHEET 2 OF 2

EV. AI	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		<p>0.6-0.5 GSPAL + 9.8 14.5</p>				
		<p>sand with silt black fine grained subangular moist to dry poorly graded</p>	<p>comp 20.5 ppm</p> <p>HS = 420 ppm</p>			
		<p>4.0 5.0-7.5 sand with silt pinkish gray 7.5 to 7/2 fine grained subangular moist</p>	<p>comp = 275 ppm</p> <p>HS = 2666 ppm</p>			
		<p>7.5-9.0 silty sand black m fine grained subangular saturated to moist</p>	<p>comp = 575 ppm</p> <p>HS = 2060 ppm</p>			
						<p>water table ~ 16.4 BLS</p>

10-11-5

A vertical ruler with a scale from 0 to 10 centimeters. The ruler is marked in millimeters, with major ticks every centimeter and minor ticks every millimeter. The scale is oriented vertically, with 0 at the top and 10 at the bottom. The ruler is black with white markings and text.

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-SV2INSTALLATION START: DATE: 06/25/02 TIME: 0840INSTALLATION FINISH: DATE: 06/25/02 TIME: 095

MATERIAL SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK:	TYPE: <u>DSI #2</u>	QUANTITY: <u>175 lbs</u>
BENTONITE SEAL:	TYPE: <u>sure seal</u>	QUANTITY: <u>20 lbs</u>
GROUT:	TYPE: <u>NA</u>	QUANTITY: <u>NA</u>

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.020 SLOT CONFIGURATION: slotted horizontally
 TOTAL OPEN AREA PER FOOT OF SCREEN: _____
 OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17
 SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC
 MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: filter sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17
 SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC
 MANUFACTURER: DSI

JOINT DESIGN AND COMPOSITION: flush treadedCENTRALIZERS DESIGN AND COMPOSITION: NONEDESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: _____ COMPOSITION: _____

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Well installed on 06/20/02 was drilled
out because surge block broke in well
and could not be recovered

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,

)? YES ☒ NO ☐Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES ☒ NO ☐Deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 0

RECORDED BY:

W. H. P. H. 06/25/02

QA CHECK BY:

Y. L. L. 06/25/02

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-SV-2


BEGIN:

END:

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



1W DRILLING LOG		DISTRICT USACE - Savannah		HOLE NUMBER 76-A3-Q1	
COMPANY NAME, SAIC		2. DRILL SUBCONTRACTOR: M. Her		SHEET 1 OF 1	
PROJECT: WY 257-261		4. LOCATION: AAFE's Car Core Center			
NAME OF DRILLER: T. Warren		6. MANUFACTURERS DESIGNATION OF DRILL: Mobile B-57			
7. TYPES AND TYPES OF DRILLING SAMPLING EQUIPMENT: 4 1/2" hollow stem auger, CME 5 continuous sampling		8. HOLE LOCATION:			
		9. SURFACE ELEVATION:			
		10. DATE STARTED: 6-20-02		11. DATE COMPLETED: 6-20-02	
OVERBURDEN THICKNESS: NA		15. DEPTH GROUNDWATER ENCOUNTERED: 3.9'			
DEPTH DRILLED INTO ROCK: NA		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
TOTAL DEPTH OF HOLE: 40.5'		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):			
GEOTECHNICAL SAMPLES: NA		DISTURBED		UNCISTURBED	
SAMPLES FOR CHEMICAL ANALYSIS		VOC	METALS	OTHER (SPECIFY)	OTHER (SPECIFY)
		BTEX	Lead		
EXPOSITION OF HOLE		BACKFILLED	MONITORING WELL	OTHER (SPECIFY)	21. TOTAL CORE RECOVERY %
			2" Air logging well		
ON SKETCH/COMMENTS: See map, page 5		21. SIGNATURE OF INSPECTOR: Benjamin J. [Signature]			
		SCALE:			

51

HTRW DRILLING LOG					HOLE NUMBER
ECT: VST's 257-361		INSPECTOR JKL			811-01
SHEET 1 OF 1					
DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	Asphalt & gravel				Augered to 3'
1	CLAYEY SAND (SC) 10% clay, medium grained, firm, moist, low plasticity, Brown, 10YR-5/3	406 ppm 1639			
2					
3	SAND (SP), very fine to fine grained, dry, soft, light gray 10YR-7/1				
4	Same as above				Augered to 8'
5	Grinding to Moist				
6	SANDY SILT (ML) 30% very fine sand, firm, moist, Very Dark Brown, 10YR-2/2	>2000 ppm 1651	JKL		
7	No Recovery				
8	Same as above.	>3000 ppm 1708			Augered to 13'
9	Wet at 8.9'				$\frac{V}{\frac{1}{2}}$

110-0115
10-10-01

552

HTRW DRILLING LOG					HOLE NUMBER
LIST 257-26-1		INSPECTOR JKL		SHEET 2 OF 4	
DEPTH (ft)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH. SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
11	SILTY SAND (SM) 80% silt, fine to medium grained, firm, wet, Dark Red 10R-3/6				
12					
13					Discontinue sampling and auger to 35.5' with a wooden plug in the hard auger
14					
15					
16					
17					
18					
19					

10-06-91

10-06-91

53

HTRW DRILLING LOG

ECT: 0194 357-261 INSPECTOR JKH HOLE NUMBER 10-17-91 SHEET 3 OF 4

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
11 12 13 14 15 16 17 18 19					No description

10-17-91

10-17-91

HTRW DRILLING LOG

JECT: 16T3 257-261

INSPECTOR JKL

HOLE NUMBER 16-45-01

SHEET 4 OF 7

V. J	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
31						
32						
33						
34						
35						
36		Bottom of hole = 35.5' - JKL				
37						
38						
39						

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS-01

INSTALLATION START: DATE: 6-20-02 TIME: 1620

INSTALLATION FINISH: DATE: 6-20-02 TIME: 1915

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DST #2 sand QUANTITY: 6 50lb bags
BENTONITE SEAL: TYPE: 3/8" bentonite pellets QUANTITY: 1/2 bucket
GROUT: TYPE: Portland Cement Grout QUANTITY: _____

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): .020" SLOT CONFIGURATION: horizontal cut

TOTAL OPEN AREA PER FOOT OF SCREEN: _____

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: _____

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: #2 sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: _____

JOINT DESIGN AND COMPOSITION: Flush Threads

CENTRALIZERS DESIGN AND COMPOSITION: N/A

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" square COMPOSITION: Steel Flush Mount

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Augered too deep - filled in with filter pack sand.

all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [X] NO []

all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES [X] NO []

distortion or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES [X] NO []

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 40 gal

ORDERED BY: [Signature]

QA CHECK BY: [Signature]

17-06-02

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-A5-01


BEGIN: 6-20-02
1630

END: 6-20-02
1915

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNIT:

DATUM/UNITS:



[illegible]

$\frac{1}{2} \cdot \frac{1}{2} = \frac{1}{4}$
 $\frac{1}{4} \cdot \frac{1}{4} = \frac{1}{16}$
 $\frac{1}{16} \cdot \frac{1}{16} = \frac{1}{256}$
 $\frac{1}{256} \cdot \frac{1}{256} = \frac{1}{65536}$
 $\frac{1}{65536} \cdot \frac{1}{65536} = \frac{1}{4294967296}$
 $\frac{1}{4294967296} \cdot \frac{1}{4294967296} = \frac{1}{18446744073709551616}$
 $\frac{1}{18446744073709551616} \cdot \frac{1}{18446744073709551616} = \frac{1}{340282366920938463463374607431768211456}$
 $\frac{1}{340282366920938463463374607431768211456} \cdot \frac{1}{340282366920938463463374607431768211456} = \frac{1}{116319045153313177352692598348072711328151740387402910362341$

HTRW DRILLING LOG		DISTRICT: USACE - Savannah		HOLE NUMBER K-A5-02	
1. COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: M. Her		3. SHEET L OF 1	
4. PROJECT: UGT's 257-261		5. LOCATION: AAFE's Coc Coc Center, Ft. Stewart, GA			
6. NAME OF DRILLER: T. Warren		7. MANUFACTURER'S DESIGNATION OF DRILL: Mobile B-57			
8. BITS AND TYPES OF DRILLING AND SAMPLING EQUIPMENT: 4 1/2" hollow stem Augers		9. HOLE LOCATION:			
10. SURFACE ELEVATION:		11. DATE STARTED: 6-24-02 12. DATE COMPLETED: 6-24-02			
13. OVERBURDEN THICKNESS: NA		14. DEPTH GROUNDWATER ENCOUNTERED:			
15. DEPTH DRILLED INTO ROCK: NA		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
17. TOTAL DEPTH OF HOLE: 33'		18. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):			
19. GEOTECHNICAL SAMPLES: NA		20. DISTURBED		21. UNDISTURBED	
22. SAMPLES FOR CHEMICAL ANALYSIS: NA		VOC		METALS	
23. DEPOSITION OF HOLE		BACKFILLED		MONITORING WELL	
24. LOCATION SKETCH/COMMENTS: See map on page 5		25. OTHER (SPECIFY):		26. OTHER (SPECIFY):	
27. SCALE:		28. SIGNATURE OF INSPECTOR: Romm		29. TOTAL CORE RECOVERY:	

HOLE NUMBER 3

ПРОЕКТ:

U67's 257-261

INSPECTOR

TK-

SHEET / OF 5

NSV
(A)

DEPTH

DESCRIPTION OF MATERIALS
(C)

HEADSPACE SCREENING RESULTS

GEOTECH
SAMPLE
OR CORE BOX

ANALYTICAL
SAMPLE NO.
(F)

REMARKS
(9)

This is a re-drill,
no samples collected
for Geologic Description.

Hole open to 9.5'

Re-drill 76-AS-02
due to a problem
with the installation.

HTRW DRILLING LOG

HOLE NUMBER ~~78-15-02~~ 37

ECT: 147' 357-201

INSPECTOR TKL

SHEET 2 OF 5

EV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					no logging done on 7/30/02
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

38

INSPECTOR JKL

HOLE NUMBER 18-A5-0.9

SHEET 3 OF 5

ELFV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					no logging on 7/30/02
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

39

HTRW DRILLING LOG

HOLE NUMBER

16-A6-03

SUBJECT: 15 T's 257-261

INSPECTOR

JKL

SHEET 4 OF 5

DEPT. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	31					
	32					
	33					
	34					
	35					
	36					
	37					
	38	Bottom of hole 38'				
	39					

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS-09 ①

INSTALLATION START: DATE: 6-24-09 TIME: 1250

INSTALLATION FINISH: DATE: 6-24-09 TIME: 1655

ANNULAR SPACE MATERIALS INVENTORY: Bentonite slurry - 5 gal.
 GRANULAR FILTER PACK: TYPE: DSI #2 sand QUANTITY: 3 3/4 50lb bags
 BENTONITE SEAL: TYPE: 3/8" bentonite pellets QUANTITY: 1 5 gal bucket
 GROUT: TYPE: Portland Cement QUANTITY: _____

DESCRIPTION OF WELL SCREEN: skt
 SLOT SIZE (inches): 20 #20 1/2" x 1/2" SLOT CONFIGURATION: horizontal cut
 TOTAL OPEN AREA PER FOOT OF SCREEN: _____
 OUTSIDE DIAMETER: 19' NOMINAL INSIDE DIAMETER: 17'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER: _____

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: DSI #2 sand

DESCRIPTION OF WELL CASING:
 OUTSIDE DIAMETER: 19' NOMINAL INSIDE DIAMETER: 17'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER: _____

JOINT DESIGN AND COMPOSITION: Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:
 NOMINAL INSIDE DIAMETER: 15" x 15" pipe COMPOSITION: steel

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:
heaving and sloughing sands - Tremied bentonite slurry through
heaved sands onto top of sand pack, and then placed bentonite
pellets on top of slurry.

as all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,

...)? YES ☒ NO ☐

as all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical

damage and/or defects? YES ☒ NO ☐

deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and

retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK REPLACEMENT: 50 gal

RECORDED BY: [Signature] 6-24-09

QA CHECK BY: [Signature] 7/3/09

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-A5-02


BEGIN: 6-24-02
1350

END: 6-24-02
1655


COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



RW DRILLING LOG		DISTRICT USACE - Savannah		HOLE NUMBER 76-AS2	
COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: <i>Miller Drilling</i>		SHEET <i>1</i> OF <i>2</i>	
1. PROJECT: <i>AAFEs Culture Center</i>		4. LOCATION: <i>see map</i>			
3. NAME OF DRILLER: <i>Paul Gibson</i>		6. MANUFACTURERS DESIGNATION OF DRILL <i>MOBIL B-57</i>			
5. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT: <i>8-57 8 1/4 (OD) Augers Hollow stem CMC Spoon</i>		8. HOLE LOCATION: <i>see map</i>			
		9. SURFACE ELEVATION:			
2. OVERBURDEN THICKNESS: <i>NA</i>		10. DATE STARTED: <i>06/21/82</i> 11. DATE COMPLETED: <i>06/21/82</i>			
3. DEPTH DRILLED INTO ROCK: <i>NA</i>		15. DEPTH GROUNDWATER ENCOUNTERED:			
4. TOTAL DEPTH OF HOLE: <i>NA WHP 35 BLS</i>		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
5. GEOTECHNICAL SAMPLES		19. TOTAL NUMBER OF CORE BOXES			
DISTURBED		UNDISTURBED			
1. SAMPLES FOR CHEMICAL ANALYSIS		VOC		METALS	
		OTHER (SPECIFY)		OTHER (SPECIFY)	
2. DISPOSITION OF HOLE		BACKFILLED		MONITORING WELL	
<i>Hit springing water</i>		OTHER (SPECIFY)		21. SIGNATURE OF INSPECTOR <i>Walter H. Pann</i>	
LOCATION SKETCH/COMMENTS		SCALE:			



HTRW DRILLING LOG						
PROJECT: <i>AA FES Car Care Center</i>				HOLE NUMBER <i>76-452</i>		
INSPECTOR <i>W. K. H. R.</i>				SHEET 2 OF 2		
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	0.0 - 0.5	Asphalt				
	0.5 - 1.5	$\frac{3.5}{5.0}$ Clayey sand $\approx 30\%$ Clay, light greenish gray 106 ϕ subangular firm to, soft, moist.	20.0 ppm core HS = 114 ppm			
	1.5 - 4.0	silty sand light gray 7.5 ϕ R & I subangular soft moist.	15.0 ppm core HS = 21			
	4.0 - 6.0	$\frac{4.0}{6.0}$ same as above				
	6.0 - 9.0	silty sand Black w/ subangular moist to saturated soft.	HS = 36 ppm 6.0 ppm core HS = 42 ppm 0.0 ppm core			

HTRW DRILLING LOG

HOLE NUMBER

JECT:

INSPECTOR

SHEET OF

IV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS82

INSTALLATION START: DATE: 06/21/02 TIME: 1530

INSTALLATION FINISH: DATE: 06/21/02 TIME: 1815

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 150 lbs

BENTONITE SEAL: TYPE: Sure Seal QUANTITY: 50 lbs

GROUT: TYPE: NA QUANTITY: NA

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.020 SLOT CONFIGURATION: slotted Horizontal

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter pack

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

JOINT DESIGN AND COMPOSITION: Flush threaded

CENTRALIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Formation Cased Above Filter Pack
and seal to 27.0 BLS TO 20 BLS
well pulled and installed at latter date

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [X] NO []

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES [X] NO []

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES [X] NO []

QUANTITY OF APPROVED WATER USED FOR FILTER PACK REPLACEMENT: 20 gallons

RECORDED BY: [Signature]

QA CHECK BY: [Signature]

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS-2


BEGIN:

END:

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:

DATUM/UNITS:



1926

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEO TECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	1.0 5.0	Sand with silt Black to gray Poorly graded sub angular soft moist fine grained	Core 20 ppm HS= 69 ppm			
	3.5 5.0	5.0 - 6.25 sand with silt light brownish gray fine grained sub angular soft moist poorly graded	Core 0.0 ppm HS= 64 ppm			
	6.25 - 8.5	silty sand Black w/ fine fine grained sub angular soft moist to saturated poorly graded	Core 120 ppm HS= 825 ppm			

HTRW DRILLING LOG

HOLE NUMBER

SUBJECT:

INSPECTOR

SHEET OF

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO (F)	REMARKS (G)
11					
12					
13					
14					
15					
16					
17					
18					
19					

Wash H. Fan 06/28/82

76-1722

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS3

INSTALLATION START: DATE: 06/24/02 TIME: 1600

INSTALLATION FINISH: DATE: 06/24/02 TIME:

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSE #2 QUANTITY: 175 lbs

BENTONITE SEAL: TYPE: Sure seal QUANTITY: 45 lbs

GROUT: TYPE: Portland type I QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.025 SLOT CONFIGURATION: Slotted Horizontal

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

JOINT DESIGN AND COMPOSITION: Flush threaded

CENTRALIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [X] NO []

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES [X] NO []

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES [X] NO []

QUANTITY OF APPROVED WATER USED FOR FILTER PACK EMPLACEMENT: 20 gallons

RECORDED BY:

QA CHECK BY:

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS3


BEGIN: 06/20/02

END: 06/20/02

COORDINATES: N:
E:


REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



W DRILLING LOG		DISTRICT: USACE - Savannah	HOLE NUMBER 76-AS4
COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: Miller Drilling	SHEET 1 OF 3
SUBJECT: AAFES CCC VSTs 257-261		4. LOCATION: 500 msp Below	
NAME OF DRILLER: Paul Gibson		6. MANUFACTURERS DESIGNATION OF DRILL: MobilP	
1. TYPE OF DRILLING EQUIPMENT: Mobile B-57 Hollow stem 4 1/2" ID Super and cone spool		8. HOLE LOCATION: 501 msp Below	
9. SURFACE ELEVATION:		10. DATE STARTED: 06/20/02	
11. DATE COMPLETED: 06/20/02		15. DEPTH GROUNDWATER ENCOUNTERED: 7 10 BLS	
16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):	
18. VERBURDEN THICKNESS: NA		19. TOTAL NUMBER OF CORE BOXES:	
20. EPTH DRILLED INTO ROCK: NA		21. TOTAL CORE RECOVERY %:	
22. TOTAL DEPTH OF HOLE: 35 BLS		23. SIGNATURE OF INSPECTOR: [Signature]	

24. GEOTECHNICAL SAMPLES		25. TOTAL NUMBER OF CORE BOXES	
26. SAMPLES FOR CHEMICAL ANALYSIS		27. TOTAL CORE RECOVERY %	
28. POSITION OF HOLE: Monitor Well		29. SIGNATURE OF INSPECTOR: [Signature]	



HTRW DRILLING LOG						HOLE NUMBER 76-A54
OBJECT: AAFES CCC		INSPECTOR: [Signature]		SHEET 2 OF 3		
DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEO TECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)	
0.0 - 0.5	Asphalt					
1.5						
1.5						
1	Sand with silt	core 12.0 ppm				
	Black 2.5N TO	HS =				
	Light Brownish gray 10% R 4%	207				
	fine grained soft moist	ppm				
2						
	sample fell	core				
	out of	209				
	spoon	ppm				
	same as above					
	Light brown					
	2. 06/20/02					
3						
4						
5	1.0/1.0					
	4.0-4.5					
	Sand with silt	core				
	Black 2.5N	210				
	fine grained	HS =				
	subangular moist	2000				
	4.5-5.0 same as	ppm				
	above except light					
	gray 10% R 7/1					
6						
	1.5/2.0					
	silty sand	core =				
	Black 2.5N	280				
	fine grained	HS =				
	subangular	2000				
	moist soft	ppm				
7						
8						
	2.0/2.0					
	same as above	core =				
		10.0				
		HS				
		2000				
		ppm				

HTRW DRILLING LOG

HOLE NUMBER 76-154

AFFS CCC

INSPECTOR *W. R. R.*

SHEET 3 OF 3

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
11	2.4/2.8 Same as above	Corr = 5.0 ppm Hg = 185 ppm			Water Table ≈ 10.0 BLS
12					
13					
14					
15	Drilled out with wood plug To 35 BLS				
16					
17					
18					
19					

76-154
EX 3

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS4

INSTALLATION START: DATE: 06/20/02 TIME: 0755

INSTALLATION FINISH: DATE: 06/20/02 TIME: 1030

WELL SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 175 lbs

BENTONITE SEAL: TYPE: Sure Seal QUANTITY: 75 lbs

GROUT: TYPE: Bentonite / Portland QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.020 SLOT CONFIGURATION: slotted Horizontal

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: DSI

FOOT OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: DSI

SCREEN DESIGN AND COMPOSITION: Flush treaded

SCREENALIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

ADDITIONAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Is well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [X] NO []

Is well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES [X] NO []

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES [X] NO []

QUANTITY OF APPROVED WATER USED FOR FILTER PACK EMPLACEMENT: 20 gallons

REVIEWED BY:

QA CHECK BY:

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS4


BEGIN: 06/20/02

END: 06/20/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNIT:

DATUM/UNITS:




3

3

3

W DRILLING LOG		DISTRICT: USACE - Savannah		HOLE NUMBER 76-ASG	
PARTY NAME: SAIC		2. DRILL SUBCONTRACTOR: Miller Drilling		SHEET 1 OF 3	
PROJECT: AAFES Ctr. Cdr's Center		4. LOCATION:			
NAME OF DRILLER: Paul Gibson		5. MANUFACTURER'S DESIGNATION OF DRILL: Mobil			
TESTS AND TYPES OF DRILLING EQUIPMENT: B-59 Mobil		6. HOLE LOCATION: 500 map Below			
TIME SPENT AND BTL CD Angus		9. SURFACE ELEVATION:			
		10. DATE STARTED: 06/19/42		11. DATE COMPLETED: 06/19/42	
OVERBURDEN THICKNESS: NA		15. DEPTH GROUNDWATER ENCOUNTERED: ~ 10 BLS			
DEPTH DRILLED INTO ROCK: NA		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED: NA			
TOTAL DEPTH OF HOLE: 36.0 BCS		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY): NA			
GEOTECHNICAL SAMPLES		DISTURBED		UNCISTURSED	
SAMPLES FOR CHEMICAL ANALYSIS		VOC		METALS	
		OTHER (SPECIFY)		OTHER (SPECIFY)	
POSITION OF HOLE: Monitor well		BACKFILLED		MONITORING WELL	
OTHER COMMENTS: At 306 ft. 14		OTHER (SPECIFY)		OTHER (SPECIFY)	
		21. SIGNATURE OF INSPECTOR: [Signature]		21. TOTAL SCORE RECOVERY	
SCALE:					



HTRW DRILLING LOG						HOLE NUMBER 76-156
PROJECT: AAFES CCC	INSPECTOR: M. H. R.					SHEET 2 OF 3
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	1.5 2.0	Sand with silt very dark brown fine grained Dry, subangular moderately graded soft	5.6 ppm FID HS = 85 ppm			
	1.0 2.0	Same as above	23 ppm FID HS = 51 ppm			
	2.0 2.0	Sand with silt yellowish orange fine grained subangular, poorly graded, soft	180 FID HS = 192 ppm			
	1.2 2.0	6.0-6.8 Same as above 6.8-7.2 Black silty sand fine grained well graded subangular, moist soft	155 FID 22000 ppm FID 86 ppm FID 22000 ppm FID			
	1.5 2.0	Same as above				
					sample @ 6-8 interval 5-10 6-8	with 66/15/02

HTRW DRILLING LOG

HOLE NUMBER 76-456
SHEET 3 OF 3

AAFE5 ECC

INSPECTOR

W. H. R.

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
11	Same as above	25ppm			water 4610 Σ 10.0 BLS
12		2200ppm			
13					
14					
15					
16					
17					
18					
19					

Drill
out to
35.5

10-1157

10-1153

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS6

INSTALLATION START: DATE: 06/19/02 TIME: 1420

INSTALLATION FINISH: DATE: 06/19/02 TIME: 1830

MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 175 lbs

BENTONITE SEAL: TYPE: Surp seal 3/8" QUANTITY: 40 lbs

GROUT: TYPE: Bentonite QUANTITY: Portland

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.020 SLOT CONFIGURATION: Horizontal slot

TOTAL OPEN AREA PER FOOT OF SCREEN: NA

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: DSI

SPACE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filler sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19' NOMINAL INSIDE DIAMETER: 0.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: DSI

MANUFACTURER: DSI

WELL DESIGN AND COMPOSITION: Flush threaded

STABILIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: NONE COMPOSITION: NONE

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease).

YES ☒ NO ☐

all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects?

YES ☒ NO ☐

distortion or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well?

YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 20 gallons

ORDERED BY: [Signature]

QA CHECK BY: [Signature]

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS6


BEGIN: 06/19/02

END: 06/19/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



HTRW DRILLING LOG						HOLE NUMBER
PROJECT: <i>ARFES CCC</i>			INSPECTOR: <i>W. H. P.</i>		SHEET 2 OF 3	
LEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		<i>0.0 - 0.4</i> <i>Asphalt D. 11A.C</i> <i>out</i>				
		<i>4.0/5.0</i>	<i>comp =</i> <i>15 ppm</i>			
		<i>0.4 - 2.4</i>	<i>45 =</i> <i>0.0 ppm</i>			
		<i>Clayey sand</i> <i>Light gray 5/8 7/1</i> <i>mottled reddish brown</i> <i>2.5 YR 5/4</i>				
		<i>fine grained, moist</i> <i>subangular to subrounded</i> <i>firm</i>				
		<i>2.4 - 4.4</i>				
		<i>silty sand</i> <i>Light gray 10 YR 7/1</i> <i>to Black N1</i> <i>fine grained, moist</i>	<i>comp =</i> <i>40 ppm</i>			
		<i>firm to soft</i>	<i>45 =</i> <i>30 ppm</i>			
		<i>spoon #2</i> <i>5.0 - 14.0</i>				
		<i>4.5/5.0</i>	<i>comp =</i> <i>180 ppm</i>			
		<i>5.0 - 6.5</i>	<i>45 =</i> <i>260 ppm</i>			
		<i>same as above</i>				
		<i>6.5 - 9.5</i>				
		<i>silty sand</i> <i>Black N1</i> <i>fine grained, moist</i> <i>firm</i>				
			<i>comp =</i> <i>225 ppm</i>			
			<i>45 =</i> <i>200 ppm</i>			

HTRW DRILLING LOG

HOLE NUMBER 76-EX/SV3

JT:

INSPECTOR

Ward H. Pinner

SHEET OF

(A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		Specimen # 3 2 1/2.5 10.0 - 12.0 silty sand Black w/1 fine grained, subangular, saturated	core = 0.0 ppm			water table ≈ 10.5
	11					
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

Ward H. Pinner 06/23/02

MONITORING WELL INSTALLATION LOG

OBJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-EX5

INSTALLATION START: DATE: 06/23/02 TIME: 0800

INSTALLATION FINISH: DATE: 06/23/02 TIME: 1630

MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSE #2 QUANTITY: 450 lbs

BENTONITE SEAL: TYPE: Sure Seal QUANTITY: 156 lbs

GROUT: TYPE: Portland Type I QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.075" #10 SLOT CONFIGURATION: Slotted Horizontal

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.35' NOMINAL INSIDE DIAMETER: 0.33

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSE

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.35' NOMINAL INSIDE DIAMETER: 0.33

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSE

WELL DESIGN AND COMPOSITION: Flush Threaded

STABILIZERS DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

ADDITIONAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Was well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Was well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES ☒ NO ☐

Was deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and removal of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK EMPLACEMENT: 50 gallons

PREPARED BY: R. H. H. H.

QA CHECK BY:

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-EX5


BEGIN: 06/23/02

END: 06/23/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-EX-5 76-SWC 76-SV3

INSTALLATION START: DATE: 06/23/02 TIME: 0830

INSTALLATION FINISH: DATE: 06/24/02 TIME: 0850

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: DSI #2 QUANTITY: 800 lbs

BENTONITE SEAL: TYPE: sure seal QUANTITY:

GROUT: TYPE: NA QUANTITY: NA

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.020 SLOT CONFIGURATION: slotted horizontally

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: filter sand 22-15 BLS

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 0.19 NOMINAL INSIDE DIAMETER: 0.17

SCHEDULE/THICKNESS: SCH 40 COMPOSITION: PVC

MANUFACTURER: DSI

Joint DESIGN AND COMPOSITION: flush threaded

Centralizers DESIGN AND COMPOSITION: NONE

DESCRIPTION OF PROTECTIVE CASING: NONE

NOMINAL INSIDE DIAMETER: COMPOSITION:

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES ☒ NO ☐

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: NONE

RECORDED BY: [Signature]
(Signature & Date)

QA CHECK BY: [Signature]
(Signature & Date)

PROJECT: AAFES Car Care Center, USTs 257-261

MONITORING WELL

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-SV3


BEGIN: 6/23/02

END: 6/23/02

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS:

DATUM/UNITS:



HTRW DRILLING LOG						
PROJECT: <u>USFS 257-261</u>			INSPECTOR: <u>JAL</u>			HOLE NUMBER: <u>26-15-028</u>
						SHEET 1 OF 4
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		Asphalt & Gravel				Augered to 3' with sampler
		CLAYEY SAND (SC) 10% clay, fine to medium grained, soft, moist, low plasticity, Yellowish Brown, 10YR-5/6	0.0 ppm 1745			
		No Recovery				
		SAND (SP), fine to very fine grained, very soft, Dry, Pale Brown, 10YR-6/9	1755 0.0 ppm			Augered to 8' with sampler
		No Recovery				
		No Recovery; sampler sides smeared with very fine sandy silt, wet the entire length of the sampler.				

HTRW DRILLING LOG

HOLE NUMBER *76-16-123*CT: *U483 257-261*INSPECTOR *JKL*SHEET *32* OF *4*

V. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					
	12					
	13					
	14					Discontinue sampling and auger down to 35.5' with a wood plug in the lead auger.
	15					
	16					
	17					
	18					
	19					

HTRW DRILLING LOG		HOLE NUMBER 1-A-08
PROJECT: 157-261	INSPECTOR JKL	SHEET 3 OF 4

HTRW DRILLING LOG		HOLE NUMBER 1-A-08
PROJECT: 157-261	INSPECTOR JKL	SHEET 3 OF 4

HTRW DRILLING LOG		HOLE NUMBER 1-A-08
PROJECT: 157-261	INSPECTOR JKL	SHEET 3 OF 4

HTRW DRILLING LOG		HOLE NUMBER 1-A-08
PROJECT: 157-261	INSPECTOR JKL	SHEET 3 OF 4

HTRW DRILLING LOG		HOLE NUMBER 1-A-08
PROJECT: 157-261	INSPECTOR JKL	SHEET 3 OF 4

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
						No description
	21					
	22					
	23					
	24					
	25					
	26					
	27					
	28					
	29					

54

INSPECTOR *JKL*

HOLE NUMBER X-AS-026

SHEET 4 OF 4

LEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	31					
	32					
	33					
	34					
	35					
	36	Bottom of hole 35.5'	JXL			
	37	Bottom of hole 37.0'				
	38					
	39					

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-75-03

INSTALLATION START: DATE: 6-21-03 TIME: 1737

INSTALLATION FINISH: DATE: 6-22-03 TIME: 1035

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK:	TYPE: D52 #2 sand	QUANTITY: 4 5lb bags
BENTONITE SEAL:	TYPE: 3/8" bentonite pellets	QUANTITY: 1/4 5 gal bucket
GROUT:	TYPE: Portland Cement Grout	QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.20" SLOT CONFIGURATION: horizontal cut

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: 1.10' NOMINAL INSIDE DIAMETER: 1.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER:

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: Filter Pack sand & formation sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: 1.19' NOMINAL INSIDE DIAMETER: 1.17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER:

JOINT DESIGN AND COMPOSITION: Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" square COMPOSITION: Steel Flush Mount

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Heaving sands - overdrilled & used lots of water.

Was all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [X] NO []

Was all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical breakage and/or defects? YES [X] NO []

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES [X] NO []

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 100 gal

RECORDED BY: [Signature]

QA CHECK BY: [Signature] 8/1/03

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-A5-08


BEGIN: 6-21-02
1737

END: 6-22-02
1035

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNIT


DATUM/UNITS:



100
100
100
100
100

100
100
100
100
100

HTRW DRILLING LOG		DISTRICT USACE - Savannah		HOLE NUMBER 76-AS-09	
1. COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: Miller		SHEET 1 OF 1	
3. PROJECT: UST's 257-261		4. LOCATION: AAFEH Car Corp Center			
5. NAME OF DRILLER: T. Warren / T. Neal		6. MANUFACTURERS DESIGNATION OF DRILL: Mobile B-57			
7. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT: 4 1/2" hollow stem augers 5' CME Continuous samplers		8. HOLE LOCATION: =			
		9. SURFACE ELEVATION:			
		10. DATE STARTED: 6-22-01		11. DATE COMPLETED: 6-22-03	
12. OVERBURDEN THICKNESS: NA		15. DEPTH GROUNDWATER ENCOUNTERED: 12.6			
13. DEPTH DRILLED INTO ROCK: NA		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
14. TOTAL DEPTH OF HOLE: 36.0'		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):			
18. GEOTECHNICAL SAMPLES: NA		DISTURBED		UNDISTURBED	
20. SAMPLES FOR CHEMICAL ANALYSIS:		VOC: BTEX		METALS: Lead	
22. DISPOSITION OF HOLE:		BACKFILLED		MONITORING WELL: 2" PVC Air Sampling Well	
				19. TOTAL NUMBER OF CORE BOXES: NA	
				21. TOTAL CORE RECOVERY:	
				23. SIGNATURE OF INSPECTOR: [Signature]	



HTRW DRILLING LOG						HOLE NUMBER
PROJECT: 15T3 257-261			INSPECTOR JKL		SHEET 1 OF 5	
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		Asphalt & Gravel				Auger to 13' 3" with sampler
		CLAYEY SAND (SC), 20% clay, low plasticity, fine to medium grained, firm, moist, Yellowish Brown, 10YR-5/6	2 JKL 1435 72000 ppm			
		SANDY SILT (ML) 20% very fine sand, soft, dry, Very Dark Gray, 10YR-3/1				
		SILTY SAND (SM) 30% silt, very fine grained, soft, dry, Yellowish Brown 10YR-5/4	1435 72000 ppm			Auger to 8' with sampler
		SANDY SILT (ML) 10% very fine sand, soft, moist, Very Dark Gray, 10YR-3/1				
		No Recovery				
		Same as above	1450 72000 ppm		76A091A	Auger to 13' with sampler

HTRW DRILLING LOG

HOLE NUMBER 257-361

ECT: 0573 257-361

INSPECTOR JKL

SHEET 3 OF 5

IV. 1A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11		1452 26 1455 1048 ppm			
	12					
		Grinding to Dark Reddish Gray 10R-3/1				
		Wet at 12.6'				
	13					
		No samples collected for Geologic Description below 13'				Discontinue sampling and auger down with plug to 35.5'
	14					
	15					
	16					
	17					
	18					
	19					

HTRW DRILLING LOG

HOLE NUMBER 11-109

PROJECT: 157-457-261

INSPECTOR *JH*

SHEET 3 OF 5

PROJECT NO.	DATE	DEPTH (ft)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		21					no samples collected for description, auger to 35.5'
		22					
		23					
		24					
		25					
		26					
		27					
		28					
		29					
		30					

HTRW DRILLING LOG

HOLE NUMBER 8-45-09

OBJECT: 151 3 357-361

INSPECTOR JKL

SHEET 4 OF 5

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	31					
	32					
	33					
	34					
	35					
	36	Bottom of hole 35.5'				
	37					
	38					
	39					

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-A5-09

INSTALLATION START: DATE: 6-22-02 TIME: 1400

INSTALLATION FINISH: DATE: 6-23-02 TIME: 1613

ANNULAR SPACE MATERIALS INVENTORY: Bentonite slurry QUANTITY: 8 gal.
 GRANULAR FILTER PACK: TYPE: DSI #2 sand QUANTITY: 5 50 lb bags
 BENTONITE SEAL: TYPE: 3/8" Bentonite Pellets QUANTITY: 4 5 gal bucket
 GROUT: TYPE: Portland cement QUANTITY:

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): .020 SLOT CONFIGURATION: horizontal cut
 TOTAL OPEN AREA PER FOOT OF SCREEN:
 OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER:

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: #2 sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER:

JOINT DESIGN AND COMPOSITION: Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" COMPOSITION: Steel Flush Mount Box

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Heaving sands - flushed down with water

Was all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES ☒ NO ☐

Was all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical breakage and/or defects? YES ☒ NO ☐

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 35 gal

RECORDED BY: AK

QA CHECK BY:

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS-029


BEGIN: 6-22-01
1400

END: 6-22-02
1613

COORDINATES: N:
E:

REFERENCE POINT: ELEVATION: DATUM/UNITS

DATUM/UNITS:



HTRW DRILLING LOG						HOLE NUMBER <i>PH-10</i>
PROJECT: <i>WIS 257-361</i>			INSPECTOR <i>JKL</i>			SHEET 1 OF 4
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		<i>Asphalt + Gravel</i>	<i>0.0 ppm</i>			<i>Augered through asphalt, inserted CME sampler and augered to 3'</i>
		<i>CLAYEY SAND (SC), 15% clay, fine to medium grained, firm, moist, Reddish Yellow, 5YR-6/6, low plasticity.</i>				
		<i>SILTY SAND (SM) fine to medium grained, 10% medium, 10% silt, dry, soft, Gray, 5YR-5/1</i>				
		<i>Same as above</i>	<i>0.0 ppm</i>			<i>Augered sampler to 8'</i>
		<i>Grading to SAND (SP), fine to very fine grained, dry, soft, Gray, 10YR-6/1</i>				
		<i>SANDY SILT (ML) 25% very fine sand, firm, moist, Black, 10YR-2/1</i>				
		<i>No Recovery</i>				
		<i>Same as above</i>	<i>0.0 ppm</i>			<i>Auger sampler to refusal at 11'</i>
		<i>Asphalt + Gravel</i>				

36

HTRW DRILLING LOG

HOLE NUMBER *7-A-10*

SHEET 2 OF 4

-T: VST, 257-261

INSPECTOR JKH

LOG NO. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		No Recovery				
	11					Discontinue sampling, Auger down to 35.5
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

HTRW DRILLING LOG						HOLE NUMBER <i>16-H5-01</i>
PROJECT: <i>15T3 257-261</i>			INSPECTOR <i>T.R.</i>		SHEET <i>3</i> OF <i>4</i>	
Y. 1	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
						<i>no description</i>
	11					
	12					
	13					
	14					
	15					
	16					
	17					
	18					
	19					

16-H5-01
16-H5-01

HTRW DRILLING LOG

HOLE NUMBER *24-15-108*

LOC: *15-13 257-361*

INSPECTOR *JL*

SHEET *7* OF *7*

LEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	31					
	32					
	33					
	34					
	35					
	36	<i>Bottom of hole 35.5'</i>				
	37					
	38					
	39					

MONITORING WELL INSTALLATION LOG

OBJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-A5-10

CALLATION START: DATE: 6-20-02 TIME: 1330

INSTALLATION FINISH: DATE: 6-30-02 TIME: 1558

ULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: D51 #2 med QUANTITY: 2 50 lb bags

BENTONITE SEAL: TYPE: 3/8" bentonite pellets QUANTITY: 18 of a 5 gal bucket

GROUT: Portland Cement Portland Grout QUANTITY: 1.00

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.20 SLOT CONFIGURATION: Horizontal cut

TOTAL OPEN AREA PER FOOT OF SCREEN: _____

OUTSIDE DIAMETER: 19' NOMINAL INSIDE DIAMETER: 17'

SCHEDULE/THICKNESS: 40 COMPOSITION: AL

MANUFACTURER: _____

≡ OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN:

DESCRIPTION OF WELL CASING: 15" #2 sand

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER: _____

T DESIGN AND COMPOSITION: *Flush Threads*

TRALIZERS DESIGN AND COMPOSITION: *NA*

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" square COMPOSITION: Steel / Flush Mount

ADDITIONAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

heaving sands - flushed down with water

all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,
YES ☒ NO ☐

Well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES ☒ NO ☐

distortion or bending of the installed well screen and casing minimized to the point of allowing the insertion and withdrawal of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 50 gal

TURNED BY: *W* *P/H*


ה'תשנ"ח

MONITORING WELL


PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AS-10	BEGIN: 6-20-08 1920	END: 6-30-08 1558
COORDINATES: N: E:	REFERENCE POINT:	ELEVATION: DATUM/UNITS:
DATUM/UNITS:		



RW DRILLING LOG		DISTRICT USACE - Savannah		HOLE NUMBER 76-AS-11	
1. COMPANY NAME: SAIC		2. DRILL SUBCONTRACTOR: Miller		SHEET 1 OF 1	
3. PROJECT: AAFE's Car Care Center		4. LOCATION: AAFE's Car Care Center			
5. NAME OF DRILLER: B. Katron		6. MANUFACTURERS DESIGNATION OF DRILL: Mobile B-52			
7. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT: 4 1/2" hollow stem auger CME 5' continuous samplers 2' split spoons		8. HOLE LOCATION: 76-AS-11			
		9. SURFACE ELEVATION:			
		10. DATE STARTED: 6-19-02		11. DATE COMPLETED: 6-19-02	
12. OVERBURDEN THICKNESS: NA		15. DEPTH GROUNDWATER ENCOUNTERED: ~13'			
13. DEPTH DRILLED INTO ROCK: NA		16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:			
14. TOTAL DEPTH OF HOLE: 35.5'		17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY): 6.45' on 6-20-02 @ 45			
18. GEOTECHNICAL SAMPLES: NA		DISTURBED		UNDISTURBED	
19. SAMPLES FOR CHEMICAL ANALYSIS		VOC	NETALS	OTHER (SPECIFY)	OTHER (SPECIFY)
		BTEX	Lead		
20. DISPOSITION OF HOLE		BACKFILLED	MONITORING WELL	OTHER (SPECIFY)	21. SIGNATURE OF INSPECTOR: <i>[Signature]</i>
			2" PVC AC Spacing Well		



ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
		Asphalt & gravel				
		No Recovery				
		SILT with SAND (ML), 10% fine sand, soft, dry, Block 10YR-2/1			76A111A	
		CLAYEY SAND, (SC), 10% sand, fine to coarse grained, Subangular, moist. Low plasticity, Firm, Yellowish Red, (5YR 5/3)				SKL
		No Recovery				
		Discontinued soil sampling and began augering.				due to problems with sampling equipment
		Cuttings consist of dense black silt described above,				

Swamp

HTRW DRILLING LOG					HOLE NUMBER	7-15-11
PROJECT: AAPET Co. Cane Center		INSPECTOR: JKL			SHEET 2 OF 4	
LEV (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11					
	12					
	13	Wet cuttings at a depth of ~ 13'				
	14					
	15					
	16					
	17					
	18					
	19					

PROJECT: <i>AAFE's Car Care Center</i>		INSPECTOR: <i>JKL</i>	HOLE NUMBER <i>7-11</i>
			SHEET <i>3</i> OF <i>4</i>

AFES Car Case Cont.

TKL

76-35-11

4

PROJECT		DATE		SHEET 2 OF 4		
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
						no description
	31					
	32					
	33					
	34					
	35					
	36					
	37					
	38					
	39					

9

QTY	DESCRIPTION OF MATERIAL	UNIT	PRICE	TOTAL
AA-15	Car Case - Central			

JKL

76-15-1

$$= 4$$

ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
31						
32						
33						
34						
35						
36		Bottom of hole 35.5'				
37						
38						
39						

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-A5-11

INSTALLATION START: DATE: 6-19-02 TIME: 1410

INSTALLATION FINISH: DATE: 6-19-02 TIME: 1630 seal installed

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK: TYPE: D51 #2 QUANTITY: 4.5 bags (50 lb each)
 BENTONITE SEAL: TYPE: Bentonite Pellets & Slurry QUANTITY: 3 gal pellets, 5 gal slurry
 GROUT: TYPE: Portland Cement QUANTITY: _____

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.20" SLOT CONFIGURATION: horizontal cut
 TOTAL OPEN AREA PER FOOT OF SCREEN: _____
 OUTSIDE DIAMETER: 1.9" 1.9' NOMINAL INSIDE DIAMETER: 1.6" 1.6' 1.7'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER: _____

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: #2 sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: 1.6" 1.7'
 SCHEDULE/THICKNESS: 40 COMPOSITION: PVC
 MANUFACTURER: _____

JOINT DESIGN AND COMPOSITION: NA - 5th Flush Threaded

CENTRALIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" pipe COMPOSITION: steel Flush Mount

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

1 pipe, moved location; soil came up against, re-augered with plug.

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease, etc.)? YES [☒] NO [☐]

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical damage and/or defects? YES [☒] NO [☐]

Is deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and retrieval of a 1.0-inch bailer throughout the entire length of the completed well? YES [☒] NO [☐]

QUANTITY OF APPROVED WATER USED FOR FILTER PACK EMPLACEMENT: 15 gal

RECORDED BY: 12 11/11


QA CHECK BY: 12 11/11

MONITORING WELL

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-AG-11	BEGIN: 6-19-02 1410	END: 6-19-02 1630
COORDINATES: N: E:	REFERENCE POINT:	ELEVATION: DATUM/UNITS
DATUM/UNITS:		



1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

HTRW DRILLING LOG		HOLE NUMBER			
CT: RAFE's Car Care Center		INSPECTOR JKL			
SHEET 1 OF 2					
DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
0	Asphalt		N/A		Augend 0-3'
1	Gravel				
2	No Recovery, chunk of asphalt blocked sampler				
3					
4	CLAYEY SAND (SC), 70% fine to coarse sand, firm, dry, low plasticity, yellowish red, 10YR 5/6				Augend 3' to 8'
5	SILT with sand, 10% fine sand, soft, dry, Dark, 10YR 3/1 0.0 ppm				
6	SAND, (SP), fine to medium grained, soft, dry Yellow, 10YR 7/6				
7	No Recovery				
8					
9	Same as above	0.0 ppm		76A13/1A	Augend 8' to 11.5'
10	SANDY SILT, ML, 30% fine sand, firm, dry to moist, Very Dark Brown, 10YR 2/2				short run due to difficulty pushing sampler through dense sandy silt.

22

HTRW DRILLING LOG		HOLE NUMBER <u>X-15-12</u>				
PROJECT: <u>AAF-23 Car Care Center</u>		INSPECTOR <u>JKL</u>				
SHEET <u>2</u> OF <u>4</u>						
ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
	11	Wet at 11.0'				∇
	12					Discontinue sampling and auger down to 35.5 with a wood plug in the lead auger.
	13					
	14					
	15					
	16					
	17					
	18					
	19					

LOT 857-361
 HIRW DRILLING LOG
 SUBJECT: AAFB Car Care Center
 INSPECTOR: JKH
 HOLE NUMBER: E-17-12
 SHEET 4 OF 4

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
31					
32					
33					
34					
35					
36	Bottom of hole 35.5'				
37					
38					
39					

10-175-01
 10-175-102
 10-175-01
 10-175-01

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-AS-12

INSTALLATION START: DATE: 6-30-02 TIME: 0805

INSTALLATION FINISH: DATE: 6-30-02 TIME: 1357

MATERIALS INVENTORY:

GRANULAR FILTER PACK:	TYPE: <u>DSE #2</u>	QUANTITY: <u>5 50 lb bags</u>
BENTONITE SEAL:	TYPE: <u>Pallats & Slurry</u>	QUANTITY: <u>1/2 5 gal. bucket</u>
GROUT:	TYPE: <u>Portland Cement</u>	QUANTITY: <u></u>

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): .020 SLOT CONFIGURATION: Horizontal cut

TOTAL OPEN AREA PER FOOT OF SCREEN:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER:

TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: #2 sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'

SCHEDULE/THICKNESS: 40 COMPOSITION: PVC

MANUFACTURER:

WELL DESIGN AND COMPOSITION: Flush Threaded

ISOLATORS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15"x15" square COMPOSITION: Steel Flush Mount

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

LC came out with the augers. Re-augered and placed well again.

all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,

YES ☒ NO ☐

all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical

damage and/or defects? YES ☒ NO ☐

separation or bending of the installed well screen and casing minimized to the point of allowing the insertion and

of a 1.0-inch bailer throughout the entire length of the completed well? YES ☒ NO ☐

QUANTITY OF APPROVED WATER USED FOR FILTER PACK ENPLACEMENT: 30 gal.

ORDERED BY: James L. H. 6-30-02

QA CHECK BY: CE 6/1/02

PROJECT: AAFES Car Care Center, USTs 257-261

MONITORING WELL

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-A5-12


BEGIN: 6-20-03
0905

END: 6-20-03
1257

COORDINATES: N:
E:

DATUM/UNITS:

REFERENCE POINT: ELEVATION: DATUM/UNITS



HTRW DRILLING LOG

DISTRICT USACE - Savannah

HOLE NUMBER

76-GA-01

1. COMPANY NAME: SAIC

2. DRILL SUBCONTRACTOR:

Miller

SHEET 1 OF 1

3. PROJECT: USF 257-261

4. LOCATION: AAFES Car Care Center

5. NAME OF DRILLER: T. Warner

6. MANUFACTURER'S DESIGNATION OF DRILL: Mobile B-57

7. SIZES AND TYPES OF DRILLING AND SAMPLING EQUIPMENT: 4 1/2" Heller Van Augers

8. HOLE LOCATION:

9. SURFACE ELEVATION:

10. DATE STARTED: 6-24-02

11. DATE COMPLETED: 6-24-02

12. OVERBURDEN THICKNESS: NA

15. DEPTH GROUNDWATER ENCOUNTERED:

13. DEPTH DRILLED INTO ROCK: NA

16. DEPTH TO WATER AND ELAPSED TIME AFTER DRILLING COMPLETED:

14. TOTAL DEPTH OF HOLE: 15.5

17. OTHER WATER LEVEL MEASUREMENTS (SPECIFY):

18. GEOTECHNICAL SAMPLES: NA

DISTURBED

UNDISTURBED

19. TOTAL NUMBER OF CORE BOXES: NA

20. SAMPLES FOR CHEMICAL ANALYSIS:

VOC

METALS

OTHER (SPECIFY)

OTHER (SPECIFY)

OTHER (SPECIFY)

21. TOTAL CORE RECOVERY:

22. DISPOSITION OF HOLE:

BACKFILLED

MONITORING WELL


OTHER (SPECIFY)

23. SIGNATURE OF INSPECTOR:

Brown

LOCATION SKETCH/COMMENTS

SCALE: NTS



ETRW DRILLING LOG

HOLE NUMBER **78 GA-0**

ST: **WTS 257-261**

INSPECTOR **JKL**

SHEET **1** OF **2**

DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
1	No samples collected for Geologic Description				Auger to 4'
2					
3					
4					
5					Auger to 8' 5" 9'
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					
101					
102					
103					
104					
105					
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					
118					
119					
120					
121					
122					
123					
124					
125					
126					
127					
128					
129					
130					
131					
132					
133					
134					
135					
136					
137					
138					
139					
140					
141					
142					
143					
144					
145					
146					
147					
148					
149					
150					
151					
152					
153					
154					
155					
156					
157					
158					
159					
160					
161					
162					
163					
164					
165					
166					
167					
168					
169					
170					
171					
172					
173					
174					
175					
176					
177					
178					
179					
180					
181					
182					
183					
184					
185					
186					
187					
188					
189					
190					
191					
192					
193					
194					
195					
196					
197					
198					
199					
200					
201					
202					
203					
204					
205					
206					
207					
208					
209					
210					
211					
212					
213					
214					
215					
216					
217					
218					
219					
220					
221					
222					
223					
224					
225					
226					
227					
228					
229					
230					
231					
232					
233					
234					
235					
236					
237					
238					
239					
240					
241					
242					
243					
244					
245					
246					
247					
248					
249					
250					
251					
252					
253					
254					
255					
256					
257					
258					
259					
260					
261					
262					
263					
264					
265					
266					
267					
268					
269					
270					
271					
272					
273					
274					
275					
276					
277					
278					
279					
280					
281					
282					
283					
284					
285					
286					
287					
288					
289					
290					
291					
292					
293					
294					
295					
296					
297					
298					
299					
300					
301					
302					
303					
304					
305					
306					
307					
308					
309					
310					
311					
312					
313					
314					
315					
316					
317					
318					
319					
320					
321					
322					
323					
324					
325					
326					
327					
328					
329					
330					
331					
332					
333					
334					
335					
336					
337					
338					
339					
340					
341					
342					
343					
344					
345					
346					
347					
348					
349					
350					
351					
352					
353					
354					</

PROJECT: <u>U47, 257-261</u>		INSPECTOR <u>SKL</u>		HOLE NUMBER <u>70-61-01</u>
DESCRIPTION		WEIRAGE		SHEET <u>2</u> OF <u>2</u>

SHEET 2 OF 2

INSPECTOR SKL

SHEET 2 OF 2

PROJ. NO.	ELEV. (A)	DEPTH (B)	DESCRIPTION OF MATERIALS (C)	HEADSPACE SCREENING RESULTS	GEOTECH SAMPLE OR CORE BOX	ANALYTICAL SAMPLE NO. (F)	REMARKS (G)
100	11						
	12						
	13						
	14						
	15						Auger to 15.5'
	16		Bottom of hole 15.5'				
	17						
	18						
	19						
	20						

MONITORING WELL INSTALLATION LOG

PROJECT: AAFES Car Care Center, USTs 257-261

DELIVERY ORDER NO: 008; 2

MONITORING WELL ID: 76-GA-01INSTALLATION START: DATE: 6-24-02 TIME: 0950INSTALLATION FINISH: DATE: 6-24-02 TIME: 0958

ANNULAR SPACE MATERIALS INVENTORY:

GRANULAR FILTER PACK:	TYPE: <u>DSI #2 sand</u>	QUANTITY: <u>5 50lb bags</u>
BENTONITE SEAL:	TYPE: <u>3/8" bentonite pellets</u>	QUANTITY: <u>3/4 5 gal. bucket</u>
GROUT:	TYPE: <u>Portland Cement</u>	QUANTITY: <u> </u>

DESCRIPTION OF WELL SCREEN:

SLOT SIZE (inches): 0.10" SLOT CONFIGURATION: Horizontal cutTOTAL OPEN AREA PER FOOT OF SCREEN: OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'SCHEDULE/THICKNESS: 40 COMPOSITION: PVCMANUFACTURER: TYPE OF MATERIAL BETWEEN BOTTOM OF BORING AND SCREEN: #2 sand

DESCRIPTION OF WELL CASING:

OUTSIDE DIAMETER: .19' NOMINAL INSIDE DIAMETER: .17'SCHEDULE/THICKNESS: 40 COMPOSITION: PVCMANUFACTURER: JOINT DESIGN AND COMPOSITION: Flush ThreadedCENTRALIZERS DESIGN AND COMPOSITION: NA

DESCRIPTION OF PROTECTIVE CASING:

NOMINAL INSIDE DIAMETER: 15" x 15" square JKL COMPOSITION: steel flush mount JKL

SPECIAL PROBLEMS ENCOUNTERED DURING WELL CONSTRUCTION AND THEIR RESOLUTION:

Pieces of plug and/or sand heaved up in stem ~ 3' - flushed down with ~ 10 gal of water

Is all well screen and casing material used for construction free of foreign matter (e.g., adhesive tape, labels, soil, grease,

)? YES [☒] NO [☐]

Is all well screen and casing material used for construction free of unsecured couplings, ruptures, and other physical

damage and/or defects? YES [☒] NO [☐]

Deformation or bending of the installed well screen and casing minimized to the point of allowing the insertion and

passage of a 1.0-inch bailer throughout the entire length of the completed well? YES [☒] NO [☐]QUANTITY OF APPROVED WATER USED FOR FILTER PACK REPLACEMENT: 10 galRECORDED BY: Kimberly Teckman 6-24-02QA CHECK BY: CP 7/30/02

PROJECT: AAFES Car Care Center, USTs 257-261

MONITORING WELL

DELIVERY ORDER NO: 008; 2

WELL NUMBER: 76-GA-01


BEGIN: 6-24-08
0850

END: 6-24-08
0959

COORDINATES: N:
E:

DATUM/UNITS:

REFERENCE POINT: ELEVATION: DATUM/UNITS



Appendix B
Well Development Forms Information
(Field Data)

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center USTs 257-261-2 DELIVERY ORDER NO: 00

Date: 4/26/02Time: 1445Well Number and Location: 76AS1Comments: soft at bottomWater Levels / Time: Initial: 7.89 / 1447Pumping: 1Final: 1Total Well Depth: Initial: 33.52 FT BTOC Final: FT BTOCDate and Time: Begin: 1 Completed: 1Development Method(S): wheel pump, surge blockTotal Quantity of Water Removed: 55 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QDØØ566	6/26/02
Specific Conductivity		
pH		
Turbidity	N/A	N/A
DO		
ORP	✓	✓

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Cat Care Center USTs 257-261 DELIVERY ORDER NO.

Date: 6/26/02

Time: 166

Well Number and Location: 76 AS 2

Comments :

Water Levels / Time: Initial: 14.26 / 1600 Pumping: /

Final: 12.35 / 1835

Total Well Depth: Initial: 32.75 FT BTOC Final: / FT BTOC

Date and Time: Begin: / Completed: /

Development Method(S): Whip pump, surge block

Total Quantity of Water Removed: 55 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD Ø Ø 566	6/26/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

WELL-DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 0082

Date: 07/29/02

Time: 0920

Well Number and Location:

AS-3

Comments :

water started a dark brown with sediment
in it cleared up to 290 NTU's light
brown color

Water Levels / Time: Initial: 0910, 7.95 Pumping: 1115, 23.03

Final: 1145,

Total Well Depth: Initial: 32.60 FT BTOC Final: 34.61 FT BTOC

Date and Time: Begin: 7/19/02, 0915 Completed: 7/29/02, 1145

Development Method(S): whale pump, surge block

Total Quantity of Water Removed: ~110 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00560	7/29/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 00

Date: 06/24/02

Time: 0850

Well Number and Location: 76-A54

Comments : water is light Brown and has sand in it

Water Levels / Time: Initial: 0835, 9.53 Pumping: 27.55, 1330

Final: /

Total Well Depth: Initial: 33.22 FT BTOC Final: / FT BTOC

Date and Time: Begin: / Completed: /

Development Method(S): whale pump

Total Quantity of Water Removed: 1807 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00566	6/24/02
Specific Conductivity	↓	↓
pH	↓	↓
Turbidity	001100003448	6/24/02
DO	QD00566	6/24/02
ORP	↓	↓

Delivery Order NO: 008

WELL NUMBER:

76-AS-4

[illegible]

RECORDED BY:

QA CHECKED BY:

Wm. Lee

28

24

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 06/23/02Time: 1330Well Number and Location: 76-ASSComments: water started light brown color
with sandWater Levels / Time: Initial: 10.17, 1515 Pumping: 1Final: 1Total Well Depth: Initial: 35.0 FT BTOC Final: 35.0 FT BTOCDate and Time: Begin: 1515, 6/23/02 Completed: 2000, 6/23/02Development Method(S): whale pumpTotal Quantity of Water Removed: 225 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	<u>Q000566</u>	<u>6/23/02</u>
Specific Conductivity	<u>↓</u>	<u>↓</u>
pH	<u>↓</u>	<u>↓</u>
Turbidity	<u>001100003448</u>	<u>6/23/02</u>
DO	<u>Q000566</u>	<u>6/23/02</u>
ORP	<u>↓</u>	<u>↓</u>

PROJECT NAME: AAFES Car Care Center; USTs 257-261

WELL NUMBER: 76-AS5

[illegible]

RECORDED BY:

QA CHECKED BY:

21

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 6/23/02

Time: 0923

Well Number and Location:

76-~~0~~AS6 AAFES

Comments :

water started a milk chocolate color
and consistency

Water Levels / Time: Initial: 4.77, 0900

Pumping: /

Final: /

Total Well Depth:

Initial: FT BTOC

Final: FT BTOC

Date and Time:

Begin: 6/23/02, 0900

Completed: 6/23/02, 1500

Development Method(S):

whale pump

Total Quantity of Water Removed: 135 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00566	6/23/02
Specific Conductivity	↓	↓
pH	↓	↓
Turbidity		
DO	QD00566	6/23/02
ORP	↓	

Delivery Order NO: Q08

WELL NUMBER: 76-A5-6

RECORDED BY:

QA CHECKED BY:

[Signature]

7

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 00

Date: ~~6/26/02~~ 7/28/021045 Time: ~~11:30~~ ASDWell Number and Location: ~~76-541~~ ASD 76-AS7Comments: very soft bottomflow rate is 0.7 gal per minuteWater Levels / Time: Initial: 1022 , 9.05 Pumping: 1050 , 28.14Final: 1300 , 28.61Total Well Depth: Initial: ~~33.19~~ 33.19 FT BTOC Final: 38 FT BTOCDate and Time: ~~7/28/02~~ 7/28/02 Begin: ~~1030~~ 1030 Completed: 7/28/02Development Method(S): whate pumpTotal Quantity of Water Removed: ≈ 100 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD 00566	7/28/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

X 5A-91

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center USTs 257-261 DELIVERY ORDER NO. 008

Date: 07/29/02

Time: 1535

Well Number and Location: A5-8

Comments: water started dark brown and cloudy cleared up to 114 NTUs

Water Levels / Time: Initial: 1315, 8.04 Pumping: 1600, 16.74
Final: 1610, 11.01

Total Well Depth: Initial: 33.40 FT BTOC Final: 34.42 FT BTOC

Date and Time: Begin: 1320, 7/29/02 Completed: 1615, 7/29/02

Development Method(S): whale pump, surge block

Total Quantity of Water Removed: 2150 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD 00566	7/29/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO:

Date: 07/28/02

Time: 15

Well Number and Location: AS-9

Comments: water started with sand and silt in it
and a ~~br~~ dark brown, at end lightened up
to 190 NTU's

Water Levels / Time: Initial: 1410 7.75 Pumping: 1645 19.90

Final: 1715 20.31

Total Well Depth: Initial: 34.05 FT BTOC Final: 35.25 FT BTOC

Date and Time: Begin: 1415 7/28/02 Completed: 1715 7/28/02

Development Method(S): whale pump surge block

Total Quantity of Water Removed: 2150 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00566	7/26/02
Specific Conductivity	N/A	
pH		
Turbidity		N/A
DO		
ORP		

7/28/02 AS-9

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center USTs 257-261 DELIVERY ORDER NO: 0

Date: 6/26/02Time: 10:20Well Number and Location: 76-AS10Comments : _____

_____Water Levels / Time: Initial: 8.64 / 10:20 Pumping: _____ / _____Final: 3 / _____Total Well Depth: Initial: 32.04 FT BTOC Final: 34.74 ^{AC} FT BTOCDate and Time: Begin: 10:20 / 6/26/02 Completed: 10:45 / 6/26/02Development Method(S): whale pump, surge blockTotal Quantity of Water Removed: ~150 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	<u>DDP 566</u>	<u>6/26/02</u>
Specific Conductivity	<u>N/A</u>	<u>N/A</u>
pH		
Turbidity		
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center USTs 257-261 DELIVERY ORDER NO: 008

Date: 6/26/02Time: 08:50Well Number and Location: 76-AS11Comments : _____

_____Water Levels / Time: Initial: 8.42 , 08:55 Pumping: _____ / _____

Final: _____ / _____

Total Well Depth: Initial: 34.40 FT BTOC Final: 34.74 FT BTOCDate and Time: Begin: 8:50 , 6/26/02 Completed: 10:45 , 6/26/02Development Method(S): whale pumpTotal Quantity of Water Removed: ~100 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00564	6/26/02
Specific Conductivity	N/A	
pH		
Turbidity		N/A
DO		
ORP		

34

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 06/24/02

Time: 1605

Well Number and Location:

76-AS12

Comments :

Light brown water with sand in at start

Water Levels / Time:

Initial: 1550 8.60

Pumping:

Final:

Total Well Depth:

Initial: 32.55 FT BTOC

Final:

FT BTOC

Date and Time:

Begin:

6/24/02 1555

Completed:

Development Method(S):

whale pump

Total Quantity of Water Removed:

2158
-125

gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	Q000566	6/24/02
Specific Conductivity	↓	↓
pH	↓	↓
Turbidity	001100003448	6/24/02
DO	Q000566	6/24/02
ORP	↓	↓

Delivery Order NO: 008

WELL NUMBER: 76-AS12

[illegible]

RECORDED BY:

QA CHECKED BY:

J. Family

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 07/26/02

Time: 1330

Well Number and Location: EX-1

Comments: water at start contained a lot of
sand and silt

Water Levels / Time: Initial: 1300, 8.19 Pumping: 1405, 11.01

Final: 1600, 10.22

Total Well Depth: Initial: 43.09 FT BTOC Final: 44.93 FT BTOC

Date and Time: Begin: 7/26/02, 1300 Completed: 7/26/02, 1600.

Development Method(S): grand Flow pump

Total Quantity of Water Removed: 500 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD 00566	7/26/02
Specific Conductivity	N/A	
pH		
Turbidity		N/A
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 0082

Date: 7/28/02 - 7/30/02

Time: _____

Well Number and Location: EX-2

Comments: water had a lot of ~~sediment~~ sediment in it
started dark brown and cloudy never
cleared up

Water Levels / Time: Initial: 8.74, 0900 Pumping: well dried, quickly

Final: well recovered completely after ~ 3 hours

Total Well Depth: Initial: _____ FT BTOC Final: 47.31 FT BTOC

Date and Time: Begin: 7/28/02, 0900 Completed: 7/30/02, 1800

Development Method(S): whale pump, Groundflows, surge
block

Total Quantity of Water Removed: 235 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD 00564	7/28/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Gar, Gar Center, USTs 257-261 DELIVERY ORDER NO. 00

Date: 7/27/02 - 7/30/02

Time: _____

Well Number and Location: EX-3

Comments: a lot of sediment in well water started dark brown and cloudy, cleared to a light brown still cloudy

Water Levels / Time: Initial: 7.56 , ~~7.90~~ Pumping: water level drops to dry
Final: well takes ~3 hours to recover completely

Total Well Depth: Initial: _____ FT BTOC Final: 48.45 FT BTOC

Date and Time: Begin: 7/27/02, ~~0900~~ Completed: 7/30/02, ~~1800~~

Development Method(s): groundflow pump, whole pump, surge block

Total Quantity of Water Removed: 314 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD00506	7/27/02
Specific Conductivity	N/A	N/A
pH		
Turbidity		
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFES Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 7/28/02 - 7/30/02

Time: _____

Well Number and Location: FX-4

Comments: started dark brown, cloudy, a lot of sediment cleared slightly

Water Levels / Time: Initial: 967, 0900 Pumping: well water dropped

Final: well recovered completely rapidly
in ~ 3 hours

Total Well Depth: Initial: _____ FT BTOC Final: 49.02 FT BTOC

Date and Time: Begin: 7/27/02, 0900 Completed: 7/30/02, 1800.

Development Method(S): grandfloss pump, whale pump
surge block

Total Quantity of Water Removed: ~ 310 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	0000566	7/28/02
Specific Conductivity	N/A	
pH		
Turbidity		N/A
DO		
ORP		

WELL DEVELOPMENT FORM

PROJECT NAME: AAFE's Car Care Center, USTs 257-261 DELIVERY ORDER NO: 008

Date: 7/28/02 - 7/30/02

Time: _____

Well Number and Location: EX-5

Comments: water started out cloudy and dark brown with a lot of sediment, cleared slightly

Water Levels / Time: Initial: 8.84 , 0900 Pumping: water level dropped
Final: well recovered in ~ 3 hrs very quickly

Total Well Depth: Initial: _____ FT BTOC Final: 47.07 FT BTOC

Date and Time: Begin: 7/27/02, 0900 Completed: 7/30/02, 1800

Development Method(S): ground flow pump, whale pump, surge block


Total Quantity of Water Removed: ~ 310 gals

FIELD MEASUREMENT	SERIAL NUMBER	DATE OF LAST CALIBRATION
Temperature	QD 00 566	7/28/02
Specific Conductivity		
pH		
Turbidity		N/A
DO		
ORP		

Appendix C


Remedial System “As-Built” Drawings

EOS
PROCONTROL A1
(INPUT)



NOT
1) A
2) /

120VAC CONTROL




NOT
1) WHI
2) BLU


EOS
PROCONTROL
MODEL A1



230VAC/3 ϕ /60HZ



NOTES:
1) ALL
2) ALL
WHITE




)


)

)

240VAC/3Ø/60HZ

N
1





Appendix D
Underground Injection Control Permit #156 Issued
by the GA DNR Dated August 29, 2002.

Georgia Department of Natural Resources

2 Martin Luther King Jr. Drive, S.E., East Tower, Atlanta, Georgia 30334
Lonice C. Barrett, Commissioner
Harold F. Reheis, Director
Environmental Protection Division
(404) 656-4713

August 29, 2002

Mr. Thomas C. Fry
Environmental Branch
Directorate of Public Works BLDG 1137
HQS 3D In DIV (Mech) and Fort Stewart
1550 Frank Cochran Drive
Fort Stewart, Georgia 31314-4927


RE: Underground Injection Control Permit #156 for injection of treated ground water and ambient air at the U. S. Army Corps of Engineers, Fort Stewarts, Building 430. Fort Stewart, Georgia (EPD-Facility ID # 9089118-1).

Dear Mr. Fry:

Enclosed is Underground Injection Control (UIC) Permit #156 for the U. S. Army Corps of Engineers, Building 430 located in Fort Stewart, Georgia. This UIC permit allows injection of treated ground water through one (1) injection well and ambient air through twelve (12) injection wells to assist with the remediation of soil and ground water contaminated with petroleum hydrocarbons at this site for up to five (5) years. The UIC permit states two (2) standard conditions and seven (7) additional conditions in the attachment.

If you have any questions about the permit, please contact Mr. Bijan Rahbar, UIC Coordinators, at (404) 656-3214.

Sincerely,


Harold F. Reheis
Director

Enclosure

cc: UIC Permit #156 File
Patty Stoll, Science Applications International Corporation
William E. Logan, EPD-USTMP

**STATE OF GEORGIA
DEPARTMENT OF NATURAL RESOURCES
ENVIRONMENTAL PROTECTION DIVISION**

INJECTION WELL OPERATING PERMIT

PERMIT NUMBER: #156

DATE ISSUED: August 29, 2002

FACILITY DATA: INJECTION WELL TYPE: CLASS V (type 5X26)

FACILITY: U.S. Army
Underground Storage Tanks 257-261
Building 430
Fort Stewart, Georgia
Liberty County

OPERATOR: U.S. Army Corps of Engineers*
1550 Frank Cochran Drive
Fort Stewart, GA 31314-4927

LOCATION: Lat: 31° 52' 17" N
Long: 81° 36' 35" W

EPD-Facility ID # 9089118-1


In accordance with the provisions of the Georgia Rules for Underground Injection Control, Chapter 391-3-6-.13, as amended 2001, this permit is issued for the operation of the herein described injection system. Unless appealed, this permit is effective thirty (30) days after its issuance and is conditioned upon the following:

- 1) The Permittee's continued compliance with the Georgia Rules for Underground Injection Control, Chapter 391-3-6-.13, the Georgia Rules for Water Quality Control (Revised) and the Georgia Rules for Safe Drinking Water (Revised); and
- 2) The Permittee's continued compliance with the Permittee's approved injection operation plan, that is part of the approved Corrective Action Plan for this site, along with provisions of officially approved plan amendments, if any.

Additional conditions 1 through 7 are attached hereto.

This revised permit is issued in accordance with the application and supplemental information received on August 13, 2002 and August 26, 2002. The injection operation plan was approved on August 29, 2002, and is based on the statements and supporting data entered herein or attached thereto, all of which are filed with the Environmental Protection Division of the Georgia Department of Natural Resources and hereby made a part of this permit.

This revised permit is subject to revocation for noncompliance with aforementioned conditions.
This revised permit expires on August 29, 2007, unless previously terminated.



Harold F. Reheis, Director, Environmental Protection Division
Georgia Department of Natural Resources

* Science Applications International Corporation, as consultant to U.S. Army, may be contacted regarding technical questions at (865) 481-4640.

**INJECTION WELL OPERATING PERMIT
ADDITIONAL CONDITIONS**

1. Permit Conditions.

- a. This revised permit is not transferable until any new operator shall agree in writing to all permit conditions. Any new operator also shall provide the Environmental Protection Division (Division) with appropriate documentation that they have adequate financial assurances to plug all existing Class V wells.
- b. If U.S. Army Corps of Engineers wishes to continue an activity regulated by this permit after the expiration of the permit, the Operator must apply for and obtain a new permit.
- c. The Operator shall report any instances of noncompliance with permit conditions to the Division in writing within five (5) working days of such noncompliance, and shall take all reasonable steps to minimize the impact on the environment resulting from noncompliance with this permit and the Georgia Rules for Underground Injection Control.
- d. The Operator shall notify the Division of any proposed changes to the performance of the treated ground water injection system in writing at least thirty (30) days prior to the change.
- e. All reports submitted to the Division shall be signed and stamped by a Georgia Registered Professional Engineer or Professional Geologist.
- f. All analyses shall be performed by a laboratory approved or accredited by EPD in accordance with the Georgia Rules for Commercial Laboratory Accreditation, Chapter 391-3-26.

2. System Parameters.

- a. This permit is issued to the Operator for the purpose of operating a treated ground water and ambient air injection system at the above referenced site to aid in remediation of soil and ground water contaminated with petroleum hydrocarbons.
- b. Number of Class V injection wells: one (1) for treated groundwater and twelve (12) for ambient air.
- c. Injected fluid: treated ground water meeting drinking water quality standards defined by Georgia Rules for Safe Drinking Water and ambient air.
- d. Maximum injection rate per well: 30 gallons of liquid/ minute (gpm)/well.
Maximum total system injection rate: 30 gpm.
Maximum injection rate per well: 3.5 cubic feet of air/min. (cfm)/well .
Maximum total system injection rate: 42 cfm.
- e. Maximum injection volume per well: 43,200 gallons of liquid/day (g/day)/well.
Maximum total system injection volume: 43,200 g/day.
Maximum injection volume per well: 5,040 cubic feet of fluid/day/well.
Maximum total system injection volume: 60,480 cf/day.

Additional Conditions, UIC Permit #156, August 29, 2002, cont.

- f. Maximum daily average injection pressure (at well head): 14.7 PSI.
3. Monitoring and Reporting Requirements.
 - a. The Operator shall report to the Underground Injection Control Program of the Division the number and exact location of all Class V injection wells it installs or plugs on a quarterly basis. The reports are to be submitted to the UIC Program in accordance with the reporting schedule stipulated by the Underground Storage Tank Management Program.
 - b. The Operator shall submit to the Division for its approval, a detailed schematic diagram and location map on any Class V injection well that is different in construction from the specifications contained in the UIC permit application, no later than 45 days prior to installation of the injection well. The Operator cannot install such a well until it receives approval from the Division.
 - c. The Operator shall submit to the UIC Program one (1) copy of any report regarding this site that the Operator is required to submit to the Underground Storage Tank Management Program.
 - d. The Operator shall submit to the UIC Program an annual report that will contain the following information.
 1. Status of the injection system operation;
 2. Results of any ground-water sampling and analyses;
 3. Results of any soil sampling and analyses;
 4. An evaluation of the plume movement through the ground water, if any;
 5. Comparisons of analyses to determine any changes in pollutant concentrations.The annual reports will be provided to the UIC Program in accordance with the schedule stipulated by the Underground Storage Tank Management Program.
4. Emergency Situations.
 - a. The Operator is to immediately notify the Division of any emergency situation that affects the injection system and describe the remedial activity that the Operator is utilizing to correct the situation.
 - b. The Operator is to immediately notify the Division when the emergency situation ceases to exist.

Additional Conditions. UIC Permit #156, August 29, 2002, cont.

5. The Operator shall grant the Division permission to enter the facility property to conduct inspections of the injection system.
6. The Operator shall maintain a copy of this permit at the facility site.
7. The Operator shall, upon termination of the injection of treated ground water through one (1) and ambient air through twelve (12) Class V injection wells at this site, properly plug and abandon all Class V wells constructed on this site in accordance with EPD's *Manual for Groundwater Monitoring* (September 1991) and notify the division within thirty (30) days of such termination and abandonment.

