## FORM 1 — SECONDARY CONTAINMENT DRAINAGE AND INSPECTION LOG

Instructions: This log must be completed each time storm water is discharged from secondary containment. <u>The storm water shall not be discharged without treatment if it has a visible sheen</u>. Furthermore, any product in the secondary containment structure must be removed.

Notify DPW immediately if any significant deficiencies are identified.

Frequency: After each significant rain event

Site/Date	Oil Present <sup>1</sup> (Y/N)	Treatment Employed (Y/N)	Drain Valve Opened (time)	Drain Valve Closed (time)	Inspector Name	Comments
		<u></u>	<u> </u>			<b>-</b>
		<u>.</u>		<u> </u>	·	<u></u>
		<u></u>				
			<b></b>	<u>e</u>	an a	<b>*</b> ******
		•				<b>6</b>
			<b>8</b>		<b>L</b>	
······································		<u></u>		<b></b>	<b></b>	
		·	<b>.</b>			4
		<u></u>	<b>.</b>	<u></u>		
. 11. 11. 11. 11. 1. <sub>1</sub>		<u></u>				<u></u>
	•					
	<u> </u>		ę	,		
		·				Rearry spectra - Million and an
· ·	•		۵	L	<u></u>	<u>.</u>
	<u></u>		•	<b></b>	<u></u>	
<i>Note:</i> 1 — product or she	en					

Revised January 2016